

Goodfellow

Serving The Needs of Science and Industry Worldwide

Au service de la Science et de l'Industrie dans le monde entier

Weltweiter Lieferant für Wissenschaft und Industrie

Metals and Alloys
Métaux et Alliages
Metalle und Legierungen

Ceramics
Céramiques
Keramiken

Polymers
Polymères
Polymere

Composites
Composites
Verbundwerkstoffe



Goodfellow Cambridge Limited

Ermine Business Park
HUNTINGDON
PE29 6WR
England

Tel: 0800 731 4653 (UK)
or +44 1480 424 800
Fax: 0800 328 7689 (UK)
or +44 1480 424 900

Goodfellow Corporation

125 Hookstown Grade Road
Coraopolis, PA 15108-9302
USA

Tel: 1-800-821-2870 (USA and Canada)
or +1 724 695 7060
Fax: 1-800-283-2020 (USA and Canada)
or +1 724 695 7063

Goodfellow SARL

229, rue Solférino
F-59000 Lille
France

Tel : 0800 917 241 (numéro vert)
or +44 1480 424 813
Fax : 0800 917 313 (numéro vert)
or +44 1480 424 900

Goodfellow GmbH

Am Edelspfad 4
D-61169 Friedberg
Germany

Tel: 0800 1000 579 (freecall)
or +44 1480 424 810
Fax: 0800 1000 580 (freecall)
or +44 1480 424 900

Goodfellow (Shanghai) Trading Co., Ltd

Fl. 23, 758 Nanjing Road West
SHANGHAI
200040

The People's Republic of China
Tel: 00 86 21 6112 1560

Standard Price List for All Meshes

CONTENTS

Introduction	4
Product Descriptions	5
Hazards Information	9
General Information	10
Order information	11
Company Details	14
Conditions of Sale	15
Metal	19
Alloy	30
Polymer	33
INDEX	38

Introduction

Goodfellow is well known as a specialist supplier of small to medium size quantities of metals, alloys, ceramics, polymers and other materials to meet the research, development and specialist production requirements of science and industry worldwide. We realise that "small" means different things to different people, but we consider small to mean any quantity from a few grammes to a few kilos.

Goodfellow offers two distinct services to meet the requirements of our customers:

- The first meets the needs of our customers who need small quantities of products from our standard range of materials within 24-48 hours.
- The second service is for those who require larger quantities or further processing of our standard products or who need an item which falls within our general area of supply expertise.

The range of materials offered by Goodfellow is extensive, as are the forms in which the various products are available. This Catalogue provides a detailed overview of our standard products which are available from stock. Full details of all of these items, including prices and technical information, can be found in our web Catalogue at www.goodfellow.com.

Materials

Metals and Alloys

Goodfellow supplies virtually all of the pure metals from Aluminium to Zirconium as well as a comprehensive range of alloys. Most are available in a variety of forms, including rod, wire and foil. The Catalogue details those materials which are available as standard products from stock. Custom-made items are also available, so please contact us if you are unable to identify the item you require.

Ceramics

The ceramic materials offered by Goodfellow have been carefully chosen and include both the established as well as more recently developed products. All are available as either standard or custom-made products in a variety of forms and sizes. The Catalogue details those items which are

available from stock. For ceramic components made to customer drawings, our Ceramic and Glass Division would be delighted to help. Please visit www.goodfellow-ceramics.com for further information.

Polymers

The range of polymers supplied by Goodfellow is broad and includes both the familiar as well as some of the more unusual or recently developed materials. The Catalogue details those items which are available from stock; please contact us if you are unable to find the item you specifically require.

Compounds & Intermetallics

Goodfellow can supply aluminides, borides and silicides as well as other intermetallics and compounds. The majority of these items are made to order and the Catalogue details those which are available. Please contact us with details of your requirements.

Composites

Some examples of these materials are listed in the Catalogue. As some of these are manufactured on a custom-made basis, please contact us with details of your requirements.

Glasses

Goodfellow offers two distinct types of glass products. The first are generally silica-based and transparent. Generally, these products are made to order for customers, so we do not list them in our Catalogue, however, they are available through the Goodfellow Ceramic and Glass Division. Please contact us with your requirements.

The second type of glass product is commonly referred to as "metallic glasses" or "glassy metals". In contrast to crystalline metals and alloys with highly ordered atomic structures, these are non-crystalline (amorphous) metals or, more usually, alloys. Our Catalogue details those glassy metals which are available from stock; please contact us if you are unable to find the item you specifically require.

Product Descriptions



Bar

A straight length of rectangular, square or oval section material.

Tolerances

Section dimensions:	≤ 10mm	± 10%
	> 10mm	± 1mm
Length:	< 100mm	± 1mm
	≥ 100mm	+ 5% / -1%



Bolt

A threaded pin that can be screwed into a nut or a tapped hole to fasten items together. Bolts are available with different head styles and also in metric and inch-threaded sizes.

Tolerances

Ceramics: ANSI B18.6.7M-1985



Chopped Fibre

Fibres cut into short lengths called cut, staple or chopped fibre.

Tolerances

Fibre diameter:	± 25%
Number of strands:	± 10%
Tex number:	± 10%
Length:	+ 5% / -1%



Crucible

A vessel in which other materials may be heated or melted, usually at high temperatures.

Tolerances

Height:	± 10%
Inside Dimensions:	± 10%
Outside Dimensions:	± 10%



Fabric

Woven fabrics are made by the regular interlacing of two arrays of yarns at right angles to each other, these being referred to as the warp and weft (see also Non-woven fabric).

Tolerances

Fabric thickness:	± 25%
Number of yarns:	± 10%
Tex number:	± 10%
Size (linear dimension):	< 100mm ± 5mm
	≥ 100mm ± 5%



Fibre

Yarns or tows consisting of several approximately parallel individual filaments, each filament usually being smaller in diameter than a monofilament. Yarns contain a defined number of filaments, typically three to several hundred; tows contain thousands of filaments whose number is only defined approximately. Both are primarily specified by their linear density measured in "tex", the weight in grammes of a 1km length of material.

Tolerances

Fibre diameter:	± 25%
Number of strands:	± 10%
Tex number:	± 10%
Length:	+ 5% / -1%



Film

A non-metallic sheet material with a thickness < 0.5mm.

Tolerances

Thickness:	± 20%
Size (linear dimension):	< 100mm ± 1mm
	≥ 100mm + 2% / -1%



Flake

Flat, irregularly shaped pieces of material. A maximum flake size is indicated but individual flakes may vary greatly in size.

Tolerances

Dimensions shown are nominal

Product Descriptions



Foam

A low density, permeable structure of cells and continuous ligaments offering a high surface area to volume ratio, and also a high strength to weight ratio. Owing to the nature of this material, dimensions are nominal.



Foil

Thin sheets of pure metal and metal alloys. Due to their fragile nature, some foils are coated on one side with an acrylic or polyester support. Where foils are supported they are indicated in the detailed item description.

Tolerances

Thickness: < 0.010mm ± 25%
 0.01-0.05mm ± 15%
 > 0.050mm ± 10%
 Size (linear dimension): < 100mm ± 1mm
 ≥ 100mm + 2% / -1%



Granule

Pellets of an approximately regular shape. Granules may vary in size and, therefore, the dimensions stated are nominal. In addition, the shape of a granule may vary from item to item.

Tolerances

Dimensions shown are nominal



Honeycomb

A cellular structure similar in appearance to natural honeycomb. Owing to the nature of this material, dimensions are nominal.



Insulated Wire

A single or multiple flexible strand of metal or alloy with an insulating sheath.

Tolerances

Wire diameter: ± 10%
 Length: + 5% / -1%
 Insulation thickness: Nominal values only



Laminate

Layers of material which have been bonded together by the use of heat, pressure and, possibly, adhesive.

Tolerances

Thickness: ± 10%
 Size (linear dimension): ≤ 100mm ± 1mm
 > 100mm + 2% / -1%



Lump

A solid piece of material with no defined shape.

Tolerances

Dimensions shown are nominal



Mesh

Mesh is available as either a woven wire or electroformed product; in all cases, the quoted aperture sizes are nominal. Wire mesh: a material which is woven from metal wires to provide a thin grid with a regular series of holes. Electroformed mesh: a product made by electroplating the mesh geometry through a mask onto a substrate which is subsequently etched away.

Tolerances

Thickness: woven: ± 10%
 electroformed: ± 20%
 Wire diameter: ± 10%
 Size (linear dimension): < 100mm ± 1mm
 ≥ 100mm + 2% / -1%



Metallised Film

Film which is coated with a metal. The thickness of the metal is measured and described in terms of the material's specific electrical resistance in ohms per square.

Tolerances

Thickness: ± 10%
 Size (linear dimension): < 100mm ± 1mm
 ≥ 100mm + 2% / -1%

Product Descriptions



Microfoil

An extremely thin sheet of metal or alloy mounted on a permanent support. This support **cannot** be removed without destroying the Microfoil.

Tolerances

Thickness: $\pm 30\%$
 Size: $\pm 20\%$



Microleaf

An extremely thin sheet of metal mounted on a removable support. Microleaf is not available for metals which are too brittle to be free standing. Microleaf is mounted on a specially treated support which allows separation of the metal film from the support. Full instructions on the method of removal are issued with each Microleaf supplied.

Tolerances

Thickness: $\pm 30\%$
 Size: $\pm 20\%$



Monofilament

A single strand of a non-metallic material.

Tolerances

Diameter: $\pm 20\%$
 Length: $+5\% / -1\%$



Non-Woven Fabric

Non-woven fabrics are made by methods other than weaving or knitting, the yarns and fibres being held together, often quite loosely, by means other than geometric interlacing. Due to the open and porous nature of this material, all other dimensions are nominal.

Tolerances

Size (linear dimension): $< 100\text{mm} \quad \pm 5\text{mm}$
 $\geq 100\text{mm} \quad \pm 5\%$



Nut

Generally a flat piece of material with a threaded hole which can be screwed onto a bolt to fasten items together. Nuts typically have a hexagonal external shape. Nuts are available in metric and inch-threaded sizes.

Tolerances

Ceramics: ANSI B18.2.4.1M-1979
 (R1995)



Powder

Small particles with an approximately defined size range. Those materials described as alloy precursors are not true alloys - they are made by sintering a blend of powders of the component metals to achieve alloying by diffusion. The resultant cake is ground and sieved to the required particle size range. Unless otherwise stated, the particle sizes shown are for guidance only. We do not guarantee either any particular size distribution between the quoted minimum and maximum sizes, or a specific particle shape.

Tolerances

Dimensions shown are nominal



Rod

A straight length of circular section material.

Tolerances

Diameter: $\leq 10\text{mm} \quad \pm 10\%$
 Polymer $+20\%/-10\%$
 Ceramic $+20\%/-10\%$

$> 10\text{mm} \quad \pm 5\%$
 Ceramic $+20\%/-10\%$
 Polymer $+20\%/-10\%$

Length: $< 100\text{mm} \quad \pm 1\text{mm}$
 $\geq 100\text{mm} \quad +5\% / -1\%$

Product Descriptions



Sheet

Flat material with a thickness >0.5mm.

Tolerances

Thickness:		± 10%
	Ceramic	± 20%
	Composite	± 20%
	Polymer	± 20%
Size (linear dimension):	< 100mm	± 1mm
	≥ 100mm	+2% / -1%



Single Crystal

A material grown as a monocrystal, generally to a specific orientation, dimension and surface finish. It may contain a dopant. Single crystals are usually made to order.

Tolerances

Orientation:	± 3°
Size:	Sizes shown are nominal



Sphere

A regular solid or hollow three-dimensional form in which every cross-section is a circle. Spheres are available with standard or precision tolerances, and can be supplied with different surface finishes depending on the material.

Tolerances

Diameter (standard):	± 5%
Diameter (precision):	see item



Sputtering Target

A high purity material used as a source for sputtering, a cold vapourisation process in which atoms are physically removed from the target surface by ion bombardment.

Tolerances

Thickness:	± 0.5mm
Size:	± 0.5mm



Tube

A hollow length of material normally circular in section. Most tubes are straight except those made of flexible polymer.

Tolerances

Outside diameter:	≤ 2mm	± 0.05mm
	Polymer	± 10%
	Ceramic	± 10%
> 5mm	± 0.1mm	
	Polymer	± 10%
	Ceramic	± 10%
Wall thickness:	> 5mm	± 5%
	Polymer	± 10%
	Ceramic	± 10%
Length:	± 10%	
	Polymer	± 20%
	Ceramic	± 20%
Length:	< 100mm	± 1mm
	≥ 100mm	+5% / -1%



Washer

A thin, flat piece of material with a hole in the middle, used in conjunction with bolts and nuts to distribute the load of a threaded fastener.

Tolerances

Ceramics:	see item
-----------	----------



Wire

A single or multiple flexible strand of pure metal or alloy.

Tolerances

Wire diameter:	± 10%
Length:	+5% / -1%

Hazards Information

HAZARDS

All materials listed in this catalogue, whatever the quantity supplied, are sold for research or development purposes. We make no warranty that the materials are fit for a particular purpose. In purchasing materials from this catalogue, customers should be aware that there may be hazards associated with their use and in the handling of them. Complete toxicological or hazard investigations are the responsibility of the customer. Ingestion or contact with the human body may be harmful. The responsibility for the safe use of our products rests with the customer. All materials should be handled by qualified personnel familiar with laboratory procedures and who are familiar with the nature of the material and any necessary precautions which should be taken in the handling, use and storage of the products. The customer shall be responsible for the control and use of the products offered in this catalogue whether alone or in combination with other articles or substances or in any other manner whatsoever.

HAZARD SYMBOLS



C

Corrosive

Chemicals which may destroy living tissue when in contact with them.



D

Dangerous when wet

Chemicals which, in contact with water or damp air, evolve highly flammable or toxic gases and vapours in dangerous quantities.



E

Explosive

Chemicals which may react exothermically without atmospheric oxygen, quickly evolving gases, and which under defined test conditions detonate, quickly deflagrate or upon heating explode when partially confined.



F+

Extremely Flammable

Chemicals which when finely divided (small particle size) are liable to ignite spontaneously.



Xn

Harmful

Chemicals which may cause death or acute or chronic damage to health when inhaled, ingested or absorbed via the skin.



F

Highly flammable

Chemicals which will ignite after contact with flame, or which will evolve highly flammable gases in contact with water.



Xi

Irritant

Non-corrosive chemicals which, through immediate, prolonged or repeated contact with the skin or mucous membrane may cause inflammation.



R

Radioactive

Chemicals which will emit ionising radiation without being subject to irradiation. General precautions for Toxic chemicals apply to those of low activity. For chemicals of medium or high activity special regulations apply.



T

Toxic

Chemicals which may cause death or acute or chronic damage to health when inhaled, ingested or absorbed via the skin.



T+

Very Toxic

Chemicals which in low quantities cause death or acute or chronic damage to health when inhaled, ingested or absorbed via the skin.

General Information

Analyses

Typical Analysis :

Where appropriate a typical analysis is given. All figures are parts per million (ppm) by weight unless otherwise stated. It must be emphasised that this data is "typical" and no guarantee is given that the material supplied will conform to these analyses. The compositions shown under alloy headings are generally weight percent. Exceptions are the glassy alloys and the rare earth magnets where the convention of using atomic ratio is followed.

Purity

Purities listed are quoted with respect to total metallic impurities. Typical analyses may give additional information about likely non-metallic impurities.

High Purity

For materials described as High Purity, the actual analysis of metallic impurities will be supplied free of charge. For other items, an actual analysis can be supplied and a charge will be made for the analysis and for the sample used.

If you require an analysis please tell us whether you require analysis of metallic impurities only or metallic and gaseous. Where an analysis is required the shipment of your order may be delayed.

Supports

Some items from our range of foils need to be supported on one side of the foil to enable both you and us to handle these very delicate materials. Two types of support can be used, the choice being governed by the material. Wherever possible we use a temporary support, a permanent support only being used when the material is brittle (for example Chromium or Manganese).

The temporary support is Acrylic, approximately 0.2mm thick. This may be removed by dissolving in 2-Propanone (Acetone).

Our permanent support is Polyester, thickness 0.125mm, which is hot-press laminated to one face of the foil. It **cannot** be removed without destroying the foil.

Microfoil is mounted on a permanent 3.5µm polyester support. This support **cannot** be removed without destroying the Microfoil.

Microleaf is mounted on a specially treated support which allows separation of the metal film from the support. Full instructions on the method of removal are issued with each Microleaf supplied.

Light Tight (LT) & Not Light Tested (NLT)

Light tight (LT) foils are supplied without visible pinholes after examination without magnification. Foils 0.025mm or more in thickness are supplied LT unless otherwise stated.

Foils less than 0.025mm thick are normally supplied Not-Light Tested (NLT), and will normally contain pinholes but may occasionally be free from pinholes. Foils less than 0.025mm in thickness can often be supplied LT but may incur additional charges. Please specify if you require LT foils

Vacuum tight

Vacuum tight foils show no detectable leakage when tested with a helium mass spectrometer with a sensitivity of 10^{-9} atm-cm³.s⁻¹.

Continuous Lengths

If you require material in continuous lengths please tell us when you place your order. Unless otherwise specified, we reserve the right to supply in more than one length.

Technical Data and Information

All information and technical data are given as a guide only. Although every effort has been made to ensure that the information is correct, no warranty is given as to its completeness or accuracy.

Tolerances

For details of our standard tolerances, please refer to the Product Description section. In many cases, closer tolerances are available but may be subject to an extra charge. If you have any special requirements it is important that you tell us at the time of ordering. This includes special tolerances, dimensional uniformity or any other special requirement which you may have (for example edge finish, packaging, labelling etc.). Please indicate precisely what is required and we shall do our best to meet your specification.

Order information

General Information

There are over 70,000 stock packs listed and if you cannot find what you need amongst them, please ask for special sizes, thicknesses, tolerances, dimensions or larger quantities. We are also able to offer many other pure metals, alloys, polymers and ceramics to special order.

Prices

All the prices listed are total (lot) prices for the sizes and quantities listed. Prices are subject to change without notice.

Prices shown include delivery except for those items marked as "special offer" or dangerous goods with transport restriction. They do not include value added tax, any import duties or local taxes.

Transport Restriction

Some of the materials supplied by Goodfellow are subject to special transport restrictions. Additional shipment charges may apply which are dependent on destination. Please check the individual item on our website or contact us for details of the charges.

If you intend to have the material transported or sent onwards please ensure that you are aware of the relevant transport restrictions.

Delivery

Delivery by door-to-door courier service of our choice is included in the prices, although alternative methods may be used depending on the materials ordered.

Split shipment

All orders are accepted for one shipment on one date to one address. A charge will be made for split shipments made at the customer's request.

Special Analysis, Supports or Tolerances

An extra charge is made for non-standard supports, alternative tolerances and certificates of analysis. The analysis is free of charge for items marked "High Purity".

Cancellations

A charge for cancellation of orders may be made. The amount will depend on the circumstances.

Express Service

An administration charge will be made for any order received for which same day shipment is requested.

Shipment

We aim to have all items listed in this catalogue in stock in the quantities and sizes listed. We can only undertake to despatch an order on a particular date. The date of delivery at the customer's address is subject to the normal variations of the delivery service used.

Despatch

Orders will normally be despatched within 48 hours of receipt.

Non delivery

If we have notified you of despatch of goods and you have not received delivery within 7 days, please contact us.

Insurance

All consignments will be insured by us against the usual risks unless we are instructed in writing to the contrary.

Export Restrictions

A UK Government export licence may be required for some items to some destinations. If the item you require needs a special export licence or an end-use statement we will inform you at the time you order.

Materials Handling

Many of our materials are extremely delicate and it is essential every care is taken when handling them. Special attention is drawn to the extreme fragility of Microfoil, Microleaf and thinner and finer materials.

All materials are carefully packed to ensure safe transport of goods to your address. We do not accept responsibility for damage caused by mishandling once the outer transit packaging has been removed.

Terms of payment

Our normal terms of payment are net 30 days from date of invoice. Any alternative terms of payment are to be agreed with us in writing at the time of placing an order. Customers may be asked to pay cash with order or cash against pro-forma invoice with their first order. In order to establish a credit account we will require details of your bankers, along with two trade references.

Order information

Credit account

We endeavour to keep our costs down and customers are requested to pay our invoices on time. We reserve the right to delay delivery if there are overdue invoices on the account. Accounts which remain unpaid beyond the due date may incur an interest charge at a rate of 2% per month.

Credit card payments

We also accept payment using the following credit and charge cards:

Mastercard, VISA, American Express, DELTA and Switch.

VAT

VAT number: GB 212 8527 79

UK

VAT will be added to the invoice at the rate ruling at the date of invoice. Where a customer is exempt, VAT will be charged unless we receive a copy of the exemption form at the time the order is placed.

EU

Customers registered for VAT who provide their local registration number will not be charged UK VAT.

Customers who are exempt from VAT will not be charged UK VAT provided we are given a copy of their exemption form at the time the goods are ordered.

Customers not registered for VAT or who fail to give us their registration number will be charged UK VAT at the current rate.

Export

All exports to countries outside the EU are zero-rated for UK VAT unless the invoice is being paid from within the EU.

Return of goods

We will only accept return of goods provided we are contacted BEFORE the goods are returned. When we agree to the return we will issue a Goods Return Number and give instructions for the method of return of the goods. Goods will not be accepted for return without a valid Goods Return Number. Due to the nature of some of our materials, it is imperative that you check any possible transport restrictions with your proposed freight company.

Claims

Great care is taken during manufacture and packing and all items are carefully inspected before shipment. Any claim in respect of short delivery, incorrect material or defective quality must be notified to us in writing within three days of delivery. Please retain ALL packaging for our inspection. Our liability for any such claim shall not exceed the cost of replacement of the goods free of charge, or crediting the customer with the invoice value thereof.

Goods ordered in error

We do not accept responsibility for customers' errors in ordering. The amount of credit for returned goods will be at our discretion. Where we accept returned goods a restocking charge will be made.

Conditions of sale

All orders, contracts and quotations are subject to our standard terms and conditions of sale.

Information and statements provided are indicative only and do not form part of any offer or contract.

Exclusions

We supply materials according to our specification. All conditions warranties and representations regarding the quality, fitness for purpose or state, size, shape, capacity or colour of goods supplied whether expressed or implied by common law or statute or otherwise are hereby expressly excluded. We shall not be liable for any damage direct or consequential arising from the use of goods supplied by us however such damage is caused, nor for delay in delivery.

Law

Customers in the USA: Contracts between Goodfellow Corporation and the customer shall be deemed to be subject in all respects to the laws of the Commonwealth of Pennsylvania, or the United States of America.

Customers in France: Contracts between Goodfellow SARL and the customer shall be deemed to be subject in all respects to French law unless otherwise agreed in writing

Customers in Germany: Contracts between Goodfellow GmbH and the customer shall be deemed to be subject in all respects to German law unless otherwise agreed in writing

Order information

Customers in the UK and all other countries: Contracts between Goodfellow Cambridge Limited and the customer shall be deemed to be subject in all respects to English law unless otherwise agreed in writing.

Copies of our General Terms and Conditions are available upon request or can be downloaded from our websites at www.goodfellow.com or www.goodfellowusa.com.

Company Details

Company Structure

The Goodfellow Group consists of five companies:

Goodfellow Cambridge Limited

Goodfellow was established in the City of London in 1946. The Company now has subsidiary operations in France, Germany and North America with the Group's research laboratories, workshop facilities & central administration located in Huntingdon, England.

Goodfellow Corporation

Established at the same time as our associate company in Germany, Goodfellow Corporation was set up to service the requirements of our customers in the USA.

Goodfellow GmbH

Since 1989, this member of the Goodfellow group of companies has been serving the needs of our German speaking customers within Europe.

Goodfellow SARL

Goodfellow established an operation in France in 1993 to meet the needs of our French-speaking customers in Europe.

Goodfellow (Shanghai) Trading Co., Ltd

Goodfellow established a representative office in Shanghai in 2006, and in 2012 followed this with the creation of a fully-fledged trading company, servicing the research and specialist manufacturing requirements of the Chinese market.

COMPANY DETAILS

Goodfellow Cambridge Limited

Ermine Business Park
HUNTINGDON
PE29 6WR
England
Registered in England and Wales no. 1188162
VAT registration GB 212 8527 79

Goodfellow Corporation

125 Hookstown Grade Road
Coraopolis, PA 15108-9302
USA
A Pennsylvania corporation
EIN 23-2557381

Goodfellow SARL

229, rue Solférino
F-59000 Lille
France
Registered in Lille : RCS : B 381 486 836
Siren : 381486836
Numéro de TVA Intracommunitaire :
FR 06 381 486 836

Goodfellow GmbH

Am Edelspfad 4
D-61169 Friedberg
Germany
Registered in Friedberg (Hessen) No. HRB 1309
Import VAT number DE112610478

Goodfellow (Shanghai) Trading Co., Ltd

Fl. 23, 758 Nanjing Road West
SHANGHAI
200040
The People's Republic of China

Conditions of Sale

1 GENERAL

1.1 In these Conditions:

1.1.1 the following expressions shall have the following meanings:-

- "Buyer" the individual firm company or other party from whom an order to supply Goods and/or Services is received by the Seller;
- "Conditions" the standard terms and conditions of sale of the Seller as set out herein and includes any additional terms and conditions of sale agreed in writing by the Seller;
- "Contract" a contract for the Supply of Goods and/or Services by the Seller to the Buyer;
- "Date of Delivery" the date on which delivery of the Goods or Services takes place pursuant to Condition 7;
- "Goods" the goods which the Seller is to supply (or, in relation to Condition 11, the goods in respect of which the Seller is to provide Services) under the Contract and includes any of them or any part of them and where the context so admits includes raw materials, processed materials and/or manufactured products whether processed or manufactured by the Seller or not;
- "Prepayment" a payment to be made by the Buyer pursuant to Condition 6.2 to be used at the Seller's discretion for the purchase of materials and/or towards the costs of labour and other costs relating to the supply of Goods;
- "Recommendations for Use" the recommendations (if any) relating to the storage, handling, application and/or use of the Goods contained in the published literature of the Seller (or, if relevant, a Supplier) or any recommendations made in Writing by an authorised representative of the Seller (or, if relevant, a Supplier);
- "Seller" Goodfellow Cambridge Limited and any subsidiary or holding company or associate (as such terms are defined in the Companies Act 1985 (as amended)) of the said company;
- "Services" the work or services or any of them to be provided by the Seller under the Contract;
- "Supplier" any person, firm or company who or which supplies materials to the Seller which make up the Goods which are to be supplied to the Buyer;

1.1.2 words importing the singular number shall include the plural and vice versa, words importing one gender shall include all genders, and words importing persons shall include bodies corporate, unincorporated associations and partnerships

- 1.2 If satisfactory references and information on the Buyer are not provided within seven days of a request therefore by the Seller, or if, following the provision of such information, the Seller is unable to obtain satisfactory trade indemnity or similar cover in respect of its dealings with the Buyer, the Seller may terminate the Contract and the rights and liabilities of the parties shall be the same as if the Contract had been cancelled in accordance with the provisions of Condition 10.2
- 1.3 The seller reserves the right to assign, sub-contract the Contract or any part thereof. The Buyer shall not be entitled to assign the benefit or burden of the Contract without the consent in writing of the Seller
- 1.4 In relation to all obligations of the Buyer under these Conditions, the time of performance is of the essence
- 1.5 The legal construction of these Conditions shall not be effected by their headings which are for convenience of reference only

2 ORDERS

- 2.1 Notwithstanding that the Seller may have given a detailed quotation or estimate either verbally or in writing no order shall be binding on the Seller unless and until it has been acknowledged in writing by the Seller or the Goods are delivered or the Services are provided by the Seller to the Buyer pursuant to the order
- 2.2 In order to avoid duplication of orders the Buyer shall be responsible for ensuring that any confirmation of an order previously placed is prominently marked as being a confirmation and not a new order. The Buyer acknowledges that any order or confirmation of order which is not so marked may be treated and accepted by the Seller as a new order to create a Contract in addition to any Contract arising out of the previously placed order
- 2.3 These Conditions are incorporated in the Contract and together with any matter set out in the Seller's quotation or acceptance/acknowledgement of order contain the entire obligations between the Seller and the Buyer. In the case of any inconsistency between any letter or quotation incorporating or referring to these Conditions and any order, letter or form of contract sent by the Buyer to the Seller, whatever may be their respective dates, the provisions of these Conditions shall prevail. In the event of the Seller entering into the Contract without the Seller having submitted a written quotation or other letter or document incorporating or referring to these Conditions but in circumstances where the Buyer has had prior notice of these Conditions then all Goods or Services supplied shall be subject to these Conditions
- 2.4 No variation of the Contract by the Buyer shall be binding upon the Seller unless made in Writing and signed on behalf of the Seller. In the event of such variation the Buyer shall indemnify and keep indemnified the Seller in full against all loss, which term shall include (but without prejudice to the generality thereof) loss of profit, costs (including the cost of labour and materials), damages, charges and expenses incurred (directly or indirectly) by the Seller as a result of such variation

2.5 Any representations (except fraudulent misrepresentations) or warranties made by or on behalf of the Seller prior to the Contract (whether verbally or in writing) are hereby expressly excluded and shall be of no effect

3 DESCRIPTION

- 3.1 Any figures, statements, descriptions, illustrations, photographs, drawings, weights or any other matters contained in the Seller's catalogues, pamphlets, price lists or advertising literature are not guaranteed to be accurate and are intended merely to represent a general picture of the Seller's products and shall not form part of the Contract nor be regarded as a warranty or representation relating to the Goods or Services
- 3.2 The Seller reserves the right to amend the specification of its products and services from time to time so that the descriptions thereof as set out in its catalogues, pamphlets, price lists or advertising literature may not be identical with those set out in the Seller's quotation and the Buyer is advised to check the specification set out in the Seller's quotation before placing an order

4 SPECIFICATIONS AND INTELLECTUAL PROPERTY

- 4.1 Where goods are supplied to the Buyer's own specification, or where standard goods of the Seller are altered in accordance with the Buyer's instructions the Buyer warrants and undertakes full responsibility for the suitability and fitness of the specification, pattern or design but also that such specification, pattern or design does not infringe any patent, trade mark, registered design, copyright or any other proprietary right of any third party and the Buyer shall indemnify and keep the Seller indemnified in full against any loss, damage or expense whatsoever (including costs) which the Seller may incur in or arising from the performance of the Contract by reason of any infringement of any such patent, trade mark, registered design, copyright or any other proprietary right
- 4.2 The Seller reserves the right to change the Buyer's specification as required to ensure that the Goods comply with any health, safety or other statutory requirement or provision and no such change by the Seller will constitute a breach of contract or impose upon the Seller any liability whatsoever
- 4.3 Unless otherwise agreed in writing, the Seller will be the sole owner of all inventions, formulations, tools, patterns, designs or other similar items and the copyright in all documents and drawings made or produced by it in preparing a quotation for the Buyer or in the course of work on any Contract with the Buyer

5 QUOTATIONS

5.1 The Seller's quotations are provisional in so far as they are subject to alteration by reference to any changes in the price of raw materials, any item to be acquired by the Seller from a third party, rates of wages, other costs of production and any other circumstances beyond the Seller's control taking place between the date of the quotation and the Buyer's placing of an order in respect thereof

6 PRICE

- 6.1 The Seller shall be entitled to adjust the Contract price of the Goods or Services whether before or after the making of the Contract in the event of any variation in the cost to the Seller of supplying the same or any part thereof caused by:-
- 6.1.1 any increase in the cost of materials required by the Seller for the completion of the Contract; or
- 6.1.2 any increase in wages or production and manufacturing costs or other overheads; or
- 6.1.3 any other reason whatsoever beyond the control of the Seller including (but without prejudice to the generality of the foregoing) fluctuations in exchange rates between monetary currencies the action of any government or any other authority or any labour problems
- 6.2 In the Seller's absolute discretion, a Prepayment in respect of the Contract may be required to be paid by the Buyer to the Seller on the terms set out in this Condition. The Prepayment shall be applied as follows:-
- 6.2.1 in the event that the Contract is performed in full by both parties the Prepayment shall be retained by the Seller in reduction of the total price payable by the Buyer under the Contract;
- 6.2.2 in the event that the Buyer is either in default of any of its obligations under the Contract or cancels or suspends the Contract in accordance with Condition 10 the Prepayment shall be set off by the Seller against its proper costs losses or damages arising in connection with the default and/or cancellation or suspension
- 6.3 Unless otherwise stated, the price set out in the Seller's quotation includes the cost of packaging, carriage, and (save as provided in Condition 6.4) insurance. In respect of supplies of Goods in the United States of America, Canada and Japan the price also includes import duties and sales taxes (if any). In respect of supplies of Goods in other countries the price does not include import duties or VAT or sales taxes which will be extra charges based on prevailing rates
- 6.4 Where the Buyer requests a particular means of delivery, the price set out in the Seller's quotation does not include insurance, which is to be arranged at the responsibility of the Buyer.

7 DELIVERY

- 7.1 Delivery of Goods shall be deemed to be effected by the Seller at the following times:-
- 7.1.1 where Goods are collected by or on behalf of the Buyer by its servants or agents, or where Goods are collected in

Conditions of Sale

- accordance with a means of delivery specifically requested by the Buyer, when the same are collected;
- 7.1.2 where delivery of the Goods is to be the responsibility of the Seller, when they arrive prior to unloading at the Buyer's premises;
- 7.1.3 where Goods are sold FOB or CIF, when they pass the ship's rail or are loaded onto the aircraft
- 7.2 Delivery of Services shall be deemed to be effected by the Seller at the time of completion by the Seller of the Services
- 7.3 Whilst the Seller will make every reasonable effort to complete the Contract by the date or dates therein specified for delivery of Goods or provision of Services such date or dates shall only constitute the times by which the Seller expects to effect such delivery and if no time is agreed delivery will be within a reasonable time but the performance of the Contract by the Seller shall not be the essence of the Contract, the Seller's failure to so deliver by the due date or dates shall not constitute a breach of Contract and the Seller shall not in any circumstances be responsible for any direct or consequential loss or damage of any kind whatsoever resulting therefrom. The Seller may wholly or partly suspend deliveries of Goods or provision of Services and the Buyer shall accept late delivery of such Goods or Services unless the Buyer has cancelled the Contract in accordance with the provisions of Condition 10.3
- 8 QUANTITIES INSTALMENTS AND STORAGE**
- 8.1 Where Goods are delivered or Services are by instalment each instalment shall be deemed to be sold under a separate Contract and the party in default in respect of any instalment shall be liable accordingly, but no default in respect of any one instalment shall effect due performance of the Contract as regards other instalments
- 8.2 The Seller will endeavour to deliver the quantity of Goods ordered and every delivery shall be deemed to comply with the order. If there is a surplus or shortage of Goods which is no more than 10% of the quantity specified in the order the Buyer shall be deemed to have accepted the Goods and shall pay for the actual quantity delivered
- 8.3 If Goods or Services are to be delivered by instalments, the Seller shall be entitled to invoice each instalment as and when delivery is made and payment for all delivered instalments shall be due notwithstanding the non-delivery of other instalments or other default by the Seller. Failure by the Buyer to make payment by the due date for any one instalment for whatever reason shall entitle the Seller to suspend deliveries of Goods or provision of Services under the Contract but without prejudice to any other right the Seller may have under any of the other provisions of these Conditions
- 8.4 Notwithstanding that risk shall have passed to the Buyer pursuant to Condition 15 the Seller may in its absolute discretion arrange for storage of the Goods either at the request of the Buyer or as a result of the failure by the Buyer to take delivery of the Goods under Condition 7. The Seller may insure the goods whilst in storage and the Buyer shall indemnify and keep indemnified the Seller in full against all costs, losses, damages and expenses whatsoever arising in connection with the storage provided for hereunder and such costs, losses, damages and expenses will be added to and form part of the price of the Goods
- 8.5 Unless otherwise agreed between the Buyer and the Seller, the Seller shall be entitled in its absolute discretion and without giving prior notice to the Buyer at the expiration of 3 months to sell or otherwise dispose of Goods kept in storage as provided in Condition 8.4
- 9 TERMS OF PAYMENT**
- 9.1 Unless otherwise agreed the price shall be due and payable at the Seller's offices 30 days after the date of the Seller's invoice
- 9.2 If the Buyer does not pay the whole or any part of the price on the required day then the Buyer shall pay to the Seller on request interest on the amount outstanding from the required day until the actual date of payment at the rate of 2% p.a. over the base rate of Barclays Bank plc from time to time in force which shall accrue on a daily basis
- 9.3 Condition 12 shall apply in the event of any alleged defect or failure in or of the Goods or Services and the Buyer shall not delay or refuse to make payment in any such event
- 9.4 The Buyer shall not be entitled to withhold payment of any amount due to the Seller by reason of any disputed claim by the Buyer in connection with the Contract nor shall the Buyer be entitled to set off against any amount payable under the Contract to the Seller any amount which is not then due and payable by the Seller or for which the Seller disputes liability
- 9.5 All payments payable to the Seller under the Contract shall become due immediately upon termination of the Contract despite any other provision.
- 10 SUSPENSION AND CANCELLATION**
- 10.1 If the Buyer shall commit any breach of the Contract and fail to remedy the same within 7 days of receiving the Seller's request in writing so to do or any distress or execution is levied upon any goods or property of the Buyer or the Buyer makes any voluntary arrangement with its creditors or becomes subject to an administration order or (being an individual or firm) becomes bankrupt or (being an incorporated company) passes a resolution for winding up (otherwise than for the purpose of amalgamation or reconstruction), or a Court makes an order to that effect, or an encumbrancer takes possession, or an administrative receiver or receiver is appointed, of any of the property or assets of the Buyer, or the Buyer ceases, or threatens to cease, to carry on business or is unable to pay its debts within the meaning of section 123 Insolvency Act, 1986, or the Seller reasonably apprehends that any of the events mentioned above is about to occur in relation to the Buyer and notifies the Buyer accordingly, the Seller may:-
- 10.1.1 stop any Goods in transit and suspend any further deliveries;

and/or

- 10.1.2 suspend work on the Contract; and/or
- 10.1.3 determine the Contract forthwith and if the Goods or Services, or any part of them have been delivered but not paid for, the price shall become immediately due and payable notwithstanding any previous agreement to the contrary but without prejudice to the Seller's right to any unpaid price for Goods or Services delivered under the Contract and to damages for loss (both direct and consequential) suffered in consequence of such determination
- 10.2 If the Buyer requires cancellation of the Contract this will only be accepted at the sole discretion of the Seller and unless otherwise agreed in writing only upon condition that any costs, charges or expenses (both direct and consequential) incurred by the Seller up to the date of cancellation and the value of all loss or damage (both direct and consequential) incurred by the Seller by reason of such cancellation will be reimbursed by the Buyer to the Seller forthwith. Acceptance by the Seller of any cancellation by the Buyer will only be binding upon the Seller if it is made in writing
- 10.3 In the event of the Seller other than in any of the circumstances set out in Condition 10.1 being prevented or hindered from completing the Contract either wholly or in part in accordance with the terms thereof for any reason whatsoever beyond its reasonable control which, for the avoidance of doubt and without prejudice to the generality of the foregoing, shall include governmental action, war, riot, civil commotion, fire, flood, epidemic, labour disputes (including labour disputes involving the work force or any part thereof of the Seller or Supplier), restraints or delays affecting shipping or carriers, licensing, exporting or importing restrictions, currency restrictions and Acts of God then further performance of the Contract shall be suspended for the period during which the Seller is so prevented provided that in the event of the Contract being suspended for a continuous period of more than 3 months then either party may give the other notice in writing to terminate the Contract forthwith and in such circumstances the Buyer shall pay for all Goods or Services supplied to the date of such termination such payment to be made on or before the last day following the month during which termination was effected. The Seller shall be under no liability whatsoever to the Buyer for any direct or consequential loss or damage suffered by the Buyer as a result of the Seller's inability to perform its obligations under the Contract in these circumstances
- 10.4 The Seller's rights contained in Condition 17 (but not the Buyer's rights) shall continue beyond the discharge of the parties' primary obligations under the Contract consequent upon its termination
- 10.5 The termination of the Contract for whatever reason will be without prejudice to the rights and duties of either party accrued prior to termination
- 11 INSPECTION AND CLAIMS FOR DEFECTS**
- 11.1 The Goods are of a highly specialised nature and must be treated with the utmost care. It is essential that the Buyer checks that they correspond in all respects with the Buyer's requirements. Any discrepancies should be notified to the Seller immediately. The Buyer undertakes to ensure that all Goods are unpacked and handled only by persons qualified to deal with such specialised products, to safeguard against injury to the Goods or to the Buyer's personnel
- 11.2 The Buyer shall inspect the Goods and carry out tests to ensure the Goods conform with the description of the Goods or Services in the Buyer's orders within 7 days of Delivery and whether or not the Buyer carries out such obligation to inspect and test no claims for non-delivery, shortages in quantity of units delivered, defective Goods or Services, non-conformity to description or partial loss or damage to Goods will be accepted by the Seller unless:-
- 11.2.1 they are notified in writing by the Buyer to the Seller within 10 days after the Date of Delivery (in the case of partial loss, damage, non-conforming or defective Goods or Services) or 14 days after the date of the invoice (in the case of non-delivery);
- 11.2.2 the Goods in respect of which a claim is made together with all the relevant packing are preserved intact as received for a period of 35 days from notification of any such claim and the Buyer permits the Seller or its servants or agents full and free right of access to inspect the Goods and investigate the claim; and
- 11.2.3 if the Buyer fails to give the appropriate notice as specified in Condition 11.2.1, the Buyer's claim will be deemed to have been waived and will be absolutely barred
- 11.3 It is in all cases the responsibility of the Buyer to ensure by testing or otherwise that the Goods are fit and suitable for the purposes for which the Buyer requires them in the conditions in which they will be used. The Buyer acknowledges that the Seller shall be under no liability of any description to the Buyer if the Goods prove to be unsuitable for whatever reason for application or use notwithstanding that the Seller may, at the request of the Buyer, have given in good faith technical or other advice in relation to the proposed application or use of the Goods and the Buyer shall indemnify and keep indemnified the Seller in full against any and all liability of any kind arising out of or connected with the application or use of the Goods
- 11.4 Section 3 Sale and Supply of Goods Act 1994 shall not apply
- 11.5 The Seller will not accept the return of Goods in any circumstances unless it has first issued a Goods return number and such number is quoted with the returned Goods
- 12 WARRANTY**
- 12.1 In substitution for all and any other rights which the Buyer might or would have had but for these Conditions and subject to Condition 11,

Conditions of Sale

the Seller shall make good by replacement any failure in the Goods or Services which results from defects in the Seller's materials or workmanship and which appear not later than 2 months after the Date of Delivery and shall replace any Goods or Services which do not conform with the description in the Buyer's order

- 12.2 Notwithstanding the provisions of Condition 12.1, in the case of a claim falling within Condition 12.1, the Seller reserves the right at its sole discretion to credit the Buyer in full the price paid by the Buyer to the Seller
- 12.3 The Seller's liability under this Condition shall automatically cease if:
- 12.3.1 the Buyer has not paid for all Goods or Services supplied under any Contract by the due date or is otherwise in breach of this or any other Contract made with the Seller; or
- 12.3.2 the Seller or its servants or agents are denied full and free right of access to the allegedly defective Goods; or
- 12.3.3 the Buyer has not properly maintained the Goods or has not complied with any Recommendations for Use; or
- 12.3.4 the defect or failure is caused by a breach by the Buyer of its undertakings and warranties contained in Condition 17; or
- 12.3.5 the Buyer has failed to notify the Seller in writing of any defect or suspected defect within 14 days of the same coming to the knowledge of the Buyer
- 12.4 The warranty set out in Condition 12.1 shall be in lieu of any warranties conditions or undertakings whether express or implied by statute, common law or otherwise howsoever which warranties, conditions and undertakings are hereby expressly excluded, except that such exclusions will not apply to any implied condition that the Seller has or will have the right to sell the Goods when the property is to pass
- 12.5 Nothing in these Conditions excludes or limits the liability of the Seller for death or personal injury caused by the Seller's negligence or fraudulent misrepresentation
- 12.6 SUBJECT TO CONDITIONS 12.4 AND 12.5
- 12.6.1 the seller's total liability in contract, tort (including negligence or breach of statutory duty), misrepresentation or otherwise, arising in connection with the performance or contemplated performance of the contract shall be limited to the price paid for the goods or services under the contract; and
- 12.6.2 the seller shall not be liable to the buyer for any indirect or consequential loss or damage (whether for loss of profit, loss of business, depletion of goodwill or otherwise), costs, expenses or other claims for consequential compensation whatsoever (however caused) which arise out of or in connection with the contract

13 CONSUMER SALES

- 13.1 Where the Goods are sold under a consumer sale (as defined by the Sale of Goods Act 1979) the statutory rights of the Buyer are not affected by these conditions

14 TITLE TO GOODS

- 14.1 Full legal and beneficial ownership of the Goods shall be retained by the Seller notwithstanding that the risk in the same shall pass to the Buyer at the time of delivery until the Seller has received payment in full in respect of
- 14.1.1 The Goods; and
- 14.1.2 All other sums which become due and owing by the Buyer to the Seller on any account whatsoever
- 14.2 Until ownership of the Goods has passed to the Buyer the Buyer shall hold the Goods in a fiduciary capacity and as bailee of the Seller and shall at all times take proper care of the same and will not obliterate or obscure any identifying mark or their packaging and will keep the Goods separate from any other goods and in such manner that they may be clearly identified as belonging to the Seller and the Buyer hereby grants to the Seller the right to enter on the Buyer's premises at any time during the continuation of the Contract to check that the Buyer is complying with the obligation contained in this Condition. The Buyer will return the Goods to the Seller if it receives a request whether verbally or in Writing so to do prior to payment in full as aforesaid having been made and the Seller will then repay any part of the purchase price it has already received in respect of the Goods less a reasonable amount in respect of its costs and expenses in connection with the Contract
- 14.3 For the purposes of Condition 14.1, the expression "the Buyer" includes any subsidiary or holding company or associate of the Buyer (as such terms are defined in the Companies Act 1985 (as amended))
- 14.4 The Seller will have the right to maintain an action against the Buyer for the price of the Goods notwithstanding that property in the Goods has not been passed

15 RISK AND INSURANCE

- 15.1 The risk in the Goods shall pass to the Buyer at the time of delivery as provided for in Condition 7
- 15.2 Notwithstanding the reservation of title contained in Condition 14, the Buyer shall insure the Goods and/or any products made wholly or partly therefrom for the full amount of the price payable under the Contract with an insurance office of repute from the time of delivery of the Goods until the date title in the Goods passes to the Buyer pursuant to Condition 14.1

16 EXPORT TERMS

- 16.1 In these Conditions "Incoterms" means the international rules for the interpretation of trade terms of the International Chamber of Commerce

as in force at the date when the Contract is made. Unless the context otherwise requires, any term or expression which is defined in or given a particular meaning by the provisions of Incoterms has the same meaning in the Contract

- 16.2 Where the Goods are supplied for export from the United Kingdom then unless otherwise agreed in writing between the Buyer and the Seller
- 16.2.1 the provisions of Incoterms shall (subject to any special terms agreed in writing between the Buyer and the Seller) apply but if there is any conflict between the provisions of Incoterms and these Conditions, the latter shall prevail.
- 16.2.2 the Buyer shall be responsible for complying with any legislation or regulations governing the importation of the Goods into the country of destination and (save in respect of the United States of America, Canada and Japan) for the payment of any duties and taxes thereon unless payment for these is included in the Contract
- 16.2.3 the Buyer shall be deemed to have satisfied itself that such Goods comply with the safety regulations of any country or state in which the Goods are to be used outside the United Kingdom and the Buyer shall indemnify and keep indemnified the Seller in full for any loss or damage whatsoever which the Seller may incur if such Goods do not comply with such safety regulations
- 16.3 The Goods shall not be used in any country other than that for which the Seller was aware they were originally ordered without the Seller's consent in writing
- 16.4 The Buyer undertakes not to offer the Goods for resale in any country notified by the Seller at or before the time the Buyer's order is placed, or to sell the Goods to any person if the Buyer knows or has reason to believe that person intends to resell the Goods in any such country

17 BUYER'S WARRANTIES

- 17.1 The Buyer warrants to the Seller that:
- 17.1.1 the Buyer will install, operate or otherwise use or store the Goods strictly in accordance with the Recommendations for Use and with all relevant or applicable statutory or other regulations governing the installation, operation, use or storage of the Goods; and
- 17.1.2 any collection vehicle, container, ship or other means of transport provided by the Buyer or any agent of the Buyer will comply with all relevant legislation and regulations relating to health and safety requirements; and
- 17.1.3 the storage and transport facilities and all parts thereof and all equipment used in connection therewith is suitable for storage (both short term and long term) and transport of the Goods and complies with any statute, regulation, bye law or other rule having the force of law and relating to the storage of goods of the nature of the Goods; and
- 17.1.4 the Buyer will ensure that the Goods are stored in conditions appropriate to goods of that nature and will comply with any recommendations as to the storage of Goods notified to it by the Seller from time to time; and
- 17.2 The Buyer shall indemnify and keep indemnified the Seller in full against any claim, loss or damage (including, without limitation, damage to the reputation of the Seller) arising directly or indirectly from any breach of the warranty contained in Condition 17.1

18 SEVERANCE

- 18.1 If at any time any one or more of the provisions or part thereof of these Conditions becomes or is invalid, illegal or unenforceable in any respect under any law or is held by a court to be invalid, illegal or unenforceable, the validity and enforceability of the remaining provisions hereof and the remainder of such provision shall not in any way be affected or impaired thereby

19 JURISDICTION

- 19.1 These Conditions and each and every Contract made pursuant to them shall be governed by and construed in all respects in accordance with the laws of England and the Seller and the Buyer hereby agree to submit to the non-exclusive jurisdiction of the English Courts

20 NOTICES

- 20.1 Any notice required or permitted to be given by either party to the other under these Conditions shall be in writing addressed to that other party at its registered office or principal place of business or such other address as may at the relevant time have been notified pursuant to this provision to the party giving notice
- 20.2 Any notice given pursuant to clause 20.1 shall be deemed to have been served:
- 20.2.1 if delivered by hand, on the first Business Day following delivery;
- 20.2.2 if sent by post, on the third Business Day after posting if the address of the recipient is in the country of despatch, otherwise on the seventh Business Day after posting;
- 20.2.3 if sent by facsimile transmission, on the first Business Day following successful transmission
- 20.3 In proving service it shall be sufficient proof in the case of a notice sent by post, that the envelope containing the same was properly stamped, addressed and placed in the post and, in the case of facsimile transmission, that it was properly addressed and successfully transmitted
- 20.4 In this Condition 20, "Business Day" shall mean any day other than Saturday, Sunday or any other day which is a public holiday in the place at which the notice is left or to which such notice is despatched

21 WAIVER

Conditions of Sale

21.1 No waiver by the Seller of any breach of any provision of the Contract by the Buyer shall be considered as a waiver of any subsequent breach

of the same or any other provision and the Seller shall not be prejudiced by any forbearance or indulgence granted by it to the Buyer

Aluminium

Al

Aluminium was discovered by Hans Oersted in Copenhagen, Denmark in 1825.

Aluminium is a silvery white reactive metal which is usually covered by a tenacious oxide coating. This renders it inert to acids, but it is attacked by alkalis. It is the most common metallic element in the earth's crust (82000 ppm) and is extracted from the hydrated oxide, Bauxite, by electrolysis of the oxide dissolved in molten sodium hexafluoroaluminate (cryolite). The metal has good thermal properties and is malleable and ductile. Aluminium and its alloys are widely used for various applications including aircraft assemblies and engine parts.

Atomic Properties

Atomic number	13
Atomic radius - Goldschmidt	0.143 nm
Atomic weight	26.98154 amu
Crystal structure	Face centred cubic
Electronic structure	Ne 3s ² 3p ¹
Photo-electric work function	4.2 eV
Thermal neutron absorption cross-section	0.232 Barns
Valences shown	3

Natural isotope distribution	Mass No.	%
	27	100

Ionisation potential	No.	eV
	1	5.99
	2	18.8
	3	28.4
	4	120
	5	154
	6	190

Physical Properties

Boiling point	2467 C
Density @20C	2.70 g cm ⁻³
Melting point	660.4 C

Electrical Properties

Electrical resistivity @20C	2.67 µOhmcm
Temperature coefficient @0-100C	0.0045 K ⁻¹
Superconductivity critical temperature	1.175 K
Thermal emf against Pt (cold 0C - hot 100C)	+0.42 mV

Thermal Properties

Coefficient of thermal expansion @0-100C	23.5 x10 ⁻⁶ K ⁻¹
Latent heat of evaporation	10800 J g ⁻¹
Latent heat of fusion	388 J g ⁻¹
Specific heat @25C	900 J K ⁻¹ kg ⁻¹
Thermal conductivity @0-100C	237 W m ⁻¹ K ⁻¹

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline	
Bulk modulus			75.2	GPa
Hardness - Vickers	21	35-48		
Poisson's ratio			0.345	
Tensile modulus			70.6	GPa
Tensile strength	50-90	130-195	MPa	
Yield strength	10-35	110-170	MPa	



Mesh

AL008722 Nominal Aperture..... **0.11mm**
 Wires/inch..... **120x120**
 Weave..... **Twill**

Wire diameter..... **0.1mm**
 Open area **27%**
 Grade **Aluminium alloy 5052**

Size

Web Code	Size
469-238-135	100 x 100 mm
216-948-992	150 x 150 mm
894-108-552	300 x 300 mm
457-907-574	500 x 500 mm

Quantity

	1pc	2pcs	5pcs
100 x 100 mm	£ 91.00	£ 108.00	£ 149.00
150 x 150 mm	£ 105.00	£ 128.00	£ 180.00
300 x 300 mm	£ 148.00	£ 189.00	
500 x 500 mm	£ 217.00		

AL008710 Nominal Aperture..... **0.38mm**
 Wires/inch..... **40x40**
 Type **Plain weave mesh**

Wire diameter..... **0.25mm**
 Open area **37%**
 Condition..... **Aluminium alloy 5052**

Size

Web Code	Size
947-063-548	150 x 150 mm
382-946-464	300 x 300 mm
868-305-669	600 x 600 mm
538-212-342	900 x 900 mm

Quantity

	1pc	2pcs	5pcs	10pcs
150 x 150 mm	£ 102.00	£ 123.00	£ 172.00	£ 230.00
300 x 300 mm	£ 134.00	£ 167.00	£ 242.00	£ 330.00
600 x 600 mm	£ 197.00	£ 257.00	£ 384.00	
900 x 900 mm	£ 260.00	£ 346.00		

Beryllium

Be

Discovered in 1797 by N.L. Vauquelin in Paris, but not extracted until 1828 by Wöhler (Berlin) and A.A.B. Bussy (Paris).

Beryllium is a light and lustrous metal which is obtained by the electrolysis of a fused halide (e.g. BeCl₂). It is resistant to attack by air or water, even at elevated temperatures (red heat). Beryllium is non-magnetic, is a good thermal conductor and is used as an alloying addition to copper or nickel, the alloys having excellent thermal, mechanical and electrical properties; in addition, when alloyed with nickel, the resultant Be/Ni alloy has the highest coefficient for secondary electron emission (12.3). Applications for pure beryllium include its use as windows in X-ray tubes and as a source of neutrons when bombarded with alpha particles, a technique used by Chadwick in 1932 in their discovery. Beryllium and its compounds are highly toxic, inhalation of the dust resulting in berylliosis, an inflammation of the lungs.

Atomic Properties

Atomic number	4
Atomic radius - Goldschmidt	0.113 nm
Atomic weight	9.01218 amu
Crystal structure	Hexagonal close packed
Electronic structure	He 2s ²
Photo-electric work function	3.4 eV
Thermal neutron absorption cross-section	0.0092 Barns
Valences shown	2

Natural isotope distribution	Mass No.	%
	9	100

Ionisation potential	No.	eV
	1	9.32
	2	18.2
	3	154
	4	218

Physical Properties

Boiling point	2470 C
Density @20C	1.848 g cm ⁻³
Melting point	1278 C

Electrical Properties

Electrical resistivity @20C	3.3 μOhmcm
Temperature coefficient @0-100C	0.0090 K ⁻¹
Superconductivity critical temperature	0.026 K

Thermal Properties

Coefficient of thermal expansion @0-100C	12.0 x 10 ⁻⁶ K ⁻¹
Latent heat of evaporation	32470 J g ⁻¹
Latent heat of fusion	1350 J g ⁻¹
Specific heat @25C	1825 J K ⁻¹ kg ⁻¹
Thermal conductivity @0-100C	201 W m ⁻¹ K ⁻¹

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline
Bulk modulus			110 GPa
Hardness - Vickers	150	200	
Poisson's ratio			0.02
Tensile modulus			318 GPa
Tensile strength	310	550	MPa
Yield strength	240	345	MPa



Mesh

BE008710

Nominal Aperture..... **0.13mm**
 Wire diameter..... **0.1mm**
 Open area **50%**

Thickness **0.025mm**
 Wires/inch..... **100**
 Type **Electro-formed mesh**



T+

Size

Web Code
 028-147-027

Quantity

Size	1pc	2pcs
5 x 5 mm	£ 223.00	£ 320.00

The edges of these electroformed meshes are solid.

Copper

Cu

Known to ancient civilisations.

Copper is a reddish coloured metal which is malleable and ductile. It has excellent thermal and electrical conductivities and good corrosion resistance. It is found in sulphide ores and as carbonate, arsenide and chloride (abundance in the Earth's crust is 50 ppm). Extraction of the metal involves roasting the ore to produce the oxide, followed by reduction and purification by electrolysis. The element is inert to non-oxidising acids but reacts with oxidising agents. In air, it will weather to produce the characteristic green patina of the carbonate. Copper will combine with oxygen on heating to produce CuO at red heat, and Cu₂O at elevated temperatures.

Pure copper has an electrical conductivity second only to that of silver and hence its main application is in the electrical industry. Copper is also the basis of many important alloys (e.g. brass, bronze and aluminium bronze) and has been traditionally considered to be one of the coinage metals, along with silver and gold, but being more common, is the least valued. It is one of the first metals ever to have been worked by man and is thought to have been mined for more than 5000 years.

Atomic Properties

Atomic number	29
Atomic radius - Goldschmidt	0.128 nm
Atomic weight	63.546 amu
Crystal structure	Face centred cubic
Electronic structure	Ar 3d ¹⁰ 4s ¹
Photo-electric work function	4.5 eV
Thermal neutron absorption cross-section	3.8 Barns
Valences shown	1, 2

Natural isotope distribution	Mass No.	%
	63	69.2
	65	30.8

Ionisation potential	No.	eV
	1	7.73
	2	20.29
	3	36.8
	4	55.2
	5	79.9
	6	103

Physical Properties

Boiling point	2567 C
Density @20C	8.96 g cm ⁻³
Melting point	1083 C

Electrical Properties

Electrical resistivity @20C	1.69 μOhmcm
Temperature coefficient @0-100C	0.0043 K ⁻¹
Thermal emf against Pt (cold 0C - hot 100C)	+0.76 mV

Thermal Properties

Coefficient of thermal expansion @0-100C	17.0 x 10 ⁻⁶ K ⁻¹
Latent heat of evaporation	4796 J g ⁻¹
Latent heat of fusion	205 J g ⁻¹
Specific heat @25C	385 J K ⁻¹ kg ⁻¹
Thermal conductivity @0-100C	401 W m ⁻¹ K ⁻¹

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline
Bulk modulus			137.8 GPa
Hardness - Vickers	49	87	
Izod toughness	58	68	J m ⁻¹
Poisson's ratio			0.343
Tensile modulus			129.8 GPa
Tensile strength	224	314	MPa
Yield strength	54	270	MPa

Copper

Cu



Mesh

CU008725	Nominal Aperture..... 0.14mm	Thickness..... 0.25mm				
	Wire diameter..... 0.115mm	Wires/inch..... 100x100				
	Open area..... 30.3%	Type..... Plain weave mesh				
Size		Quantity				
Web Code	Size	1pc	2pcs	5pcs	10pcs	
665-564-911	100 x 100 mm	£ 96.50	£ 123.00	£ 196.00	£ 232.00	
594-303-043	150 x 150 mm	£ 106.00	£ 136.00	£ 217.00	£ 261.00	
432-048-907	300 x 300 mm	£ 133.00	£ 175.00	£ 278.00		
860-435-736	600 x 600 mm	£ 189.00	£ 258.00			
110-848-353	900 x 900 mm	£ 259.00				
Coil		Width		Quantity		
Web Code	Length	1 Reel				
112-651-623	1 m			£ 295.00		

CU008705	Nominal Aperture..... 0.18mm	Wire diameter..... 0.14mm				
	Wires/inch..... 80x80	Open area..... 31%				
	Type..... Plain weave mesh					
Size		Quantity				
Web Code	Size	1pc	2pcs	5pcs	10pcs	
746-794-747	100 x 100 mm	£ 98.50	£ 126.00	£ 207.00	£ 238.00	
040-671-976	150 x 150 mm	£ 102.00	£ 131.00	£ 215.00	£ 249.00	
939-701-764	300 x 300 mm	£ 112.00	£ 146.00	£ 238.00	£ 282.00	
245-396-436	600 x 600 mm	£ 133.00	£ 175.00	£ 314.00		
908-347-905	900 x 900 mm	£ 154.00	£ 227.00			

CU008720	Nominal Aperture..... 0.2mm	Thickness..... 0.004mm				
	Wire diameter..... 0.0125mm	Wires/inch..... 118				
	Open area..... 88%	Type..... Electro-formed mesh				
Size		Quantity				
Web Code	Size	1pc	2pcs	5pcs		
182-875-908	30 x 30 mm	£ 166.00	£ 217.00	£ 319.00		
262-899-394	65 x 65 mm	£ 281.00	£ 379.00	£ 575.00		
862-420-913	130 x 130 mm	£ 494.00	£ 748.00			
802-616-692	260 x 260 mm	£ 1408.00				

CU008710	Nominal Aperture..... 0.38mm	Wire diameter..... 0.25mm				
	Wires/inch..... 40x40	Open area..... 37%				
	Type..... Plain weave mesh					
Size		Quantity				
Web Code	Size	1pc	2pcs	5pcs	10pcs	
695-468-192	100 x 100 mm	£ 94.50	£ 121.00	£ 192.00	£ 227.00	
933-513-048	150 x 150 mm	£ 103.00	£ 133.00	£ 211.00	£ 253.00	
689-131-642	300 x 300 mm	£ 128.00	£ 168.00	£ 267.00	£ 344.00	
141-456-896	600 x 600 mm	£ 178.00	£ 239.00	£ 495.00		

Gold

Au

This metal has been known since prehistoric times
 Gold is a soft metal with a characteristic yellow colour. It is the most malleable and ductile of any element. It is unaffected by air, water, alkalis and acids, with the exception of "aqua regia", HNO₃/HCl. The fact that it is chemically unreactive means that it is often found in its natural state. It is a good thermal and electrical conductor and has excellent reflective properties to both light and infrared. It has an abundance in the earth's crust of 0.0011 ppm.

Most of the metal is retained for use as bullion reserves, but some is used within the electronics and jewellery industries, where it is frequently alloyed with other elements to improve the mechanical properties of the metal (e.g. copper and silver). Other uses for the metal are as a heat reflecting coating for glass as well as as a decorative medium.

Atomic Properties		Electrical Properties			
Atomic number	79	Electrical resistivity @20C		2.20 µOhmcm	
Atomic radius - Goldschmidt	0.144 nm	Temperature coefficient @0-100C		0.0040 K ⁻¹	
Atomic weight	196.9665 amu	Thermal emf against Pt (cold 0C - hot 100C)		+ 0.74 mV	
Crystal structure	Face centred cubic	Thermal Properties			
Electronic structure	Xe 4f ¹⁴ 5d ¹⁰ 6s ¹	Coefficient of thermal expansion @0-100C		14.1 x10 ⁻⁶ K ⁻¹	
Photo-electric work function	4.8 eV	Latent heat of evaporation		1738 J g ⁻¹	
Thermal neutron absorption cross-section	98.8 Barns	Latent heat of fusion		64.9 J g ⁻¹	
Valences shown	1,3	Specific heat @25C		129 J K ⁻¹ kg ⁻¹	
Natural isotope distribution	Mass No. %	Thermal conductivity @0-100C		318 W m ⁻¹ K ⁻¹	
	197 100	Mechanical Properties			
Ionisation potential	No. eV	Material condition	Soft	Hard	Polycrystalline
	1 9.22	Bulk modulus			171 GPa
	2 20.5	Hardness - Vickers	20-30	60	
Physical Properties		Poisson's ratio			0.42
Boiling point	3080 C	Tensile modulus			78.5 GPa
Density @20C	19.30 g cm ⁻³	Tensile strength	130	220	MPa
Melting point	1064.4 C	Yield strength		205	MPa

Gold

Au



Mesh

AU008721

Nominal Aperture..... **0.011mm** Thickness..... **0.004mm**
 Wire diameter..... **0.005mm** Wires/inch..... **1500**
 Open area..... **44%** Purity..... **99.9%**
 Type..... **Electro-formed mesh**

Size Web Code	Size	Quantity	
		1pc	2pcs
437-659-372	10 x 10 mm	£ 148.00	£ 191.00
899-125-481	20 x 20 mm	£ 229.00	£ 304.00
804-703-028	50 x 50 mm	£ 501.00	

Typical Analysis : Ag 300, Al 1, B 1, Bi 2, Ca 4, Cd 4, Cr 5, Cu 500, Fe 2, K 15, Mg 1, Mn 1, Na 1, Ni 100, Pb 15, Pd 7, Sb 7, Si 2, Sn 5, V 2, Zr 10.

AU008725

Nominal Aperture..... **0.04mm** Thickness..... **0.006mm**
 Wire diameter..... **0.011mm** Wires/inch..... **500**
 Open area..... **60%** Purity..... **99.9%**
 Type..... **Electro-formed mesh**

Size Web Code	Size	Quantity		
		1pc	2pcs	5pcs
729-929-971	10 x 10 mm	£ 132.00	£ 168.00	£ 242.00
525-067-831	25 x 25 mm	£ 228.00	£ 304.00	
290-503-215	50 x 50 mm	£ 469.00		

Typical Analysis : Ag 300, Al 1, B 1, Bi 2, Ca 4, Cd 4, Cr 5, Cu 500, Fe 2, K 15, Mg 1, Mn 1, Na 1, Ni 100, Pb 15, Pd 7, Sb 7, Si 2, Sn 5, V 2, Zr 10.

AU008730

Nominal Aperture..... **0.064mm** Thickness..... **0.004mm**
 Wire diameter..... **0.0125mm** Wires/inch..... **333**
 Open area..... **70%** Purity..... **99.9%**
 Type..... **Electro-formed mesh**

Size Web Code	Size	Quantity		
		1pc	2pcs	5pcs
616-585-237	10 x 10 mm	£ 98.50	£ 119.00	£ 159.00
142-974-300	25 x 25 mm	£ 152.00	£ 195.00	
579-165-476	50 x 50 mm	£ 274.00		

Typical Analysis : Ag 300, Al 1, B 1, Bi 2, Ca 4, Cd 4, Cr 5, Cu 500, Fe 2, K 15, Mg 1, Mn 1, Na 1, Ni 100, Pb 15, Pd 7, Sb 7, Si 2, Sn 5, V 2, Zr 10.

AU008710

Nominal Aperture..... **0.25mm** Wire diameter..... **0.06mm**
 Wires/inch..... **82x82** Open area..... **65%**
 Purity..... **99.9%** Type..... **Plain weave mesh**

Size Web Code	Size	Quantity		
		1pc	2pcs	5pcs
011-784-569	20 x 20 mm	£ 153.00	£ 192.00	£ 273.00
473-069-099	50 x 50 mm	£ 248.00	£ 410.00	
133-626-904	100 x 100 mm	£ 684.00		

Typical Analysis : Ag 300, Al 1, B 1, Bi 2, Ca 4, Cd 4, Cr 5, Cu 500, Fe 2, K 15, Mg 1, Mn 1, Na 1, Ni 100, Pb 15, Pd 7, Sb 7, Si 2, Sn 5, V 2, Zr 10.

Metal – Gold

Molybdenum

Mo

Discovered in 1871 by P.J. Hjelm in Uppsala, Sweden.

Molybdenum is a lustrous, silvery coloured metal which has an abundance of 1.5 ppm in the earth's crust. In many instances, it shows a resemblance to tungsten with which it tends to be paired in the transition series in the periodic table, but their chemistries tend to show more distinct differences than might be expected.

Molybdenum has a high melting point and applications for the pure metal take advantage of this; for example, the pure material is used as resistance heating elements in furnaces, as filament supports in electric lamps, and as electrodes for mercury vapour lamps. Molybdenum is used as an alloying agent in certain grades of steel, Permalloys and Stellites (a series of alloys which contain varying proportions of Cr, Co, W and Mo, are very hard and are used in cutting tools and to protect surfaces subject to heavy wear).

Atomic Properties

Atomic number	42
Atomic radius - Goldschmidt	0.140 nm
Atomic weight	95.94 amu
Crystal structure	Body centred cubic
Electronic structure	Kr 4d ⁵ 5s ¹
Photo-electric work function	4.2 eV
Thermal neutron absorption cross-section	2.65 Barns
Valences shown	2, 3, 4, 5, 6

Natural isotope distribution	Mass No.	%
	92	14.8
	94	9.3
	95	15.9
	96	16.7
	97	9.6
	98	24.1
	100	9.6

Ionisation potential	No.	eV
	1	7.10
	2	16.15
	3	27.2
	4	46.4
	5	61.2
	6	68

Physical Properties

Boiling point	4612 C
Density @20C	10.22 g cm ⁻³
Melting point	2617 C

Electrical Properties

Electrical resistivity @20C	5.7 µOhmcm
Temperature coefficient @0-100C	0.00435 K ⁻¹
Superconductivity critical temperature	0.915 K
Thermal emf against Pt (cold 0C - hot 100C)	+ 1.45 mV

Thermal Properties

Coefficient of thermal expansion @0-100C	5.1 x10 ⁻⁶ K ⁻¹
Latent heat of evaporation	6153 J g ⁻¹
Latent heat of fusion	290 J g ⁻¹
Specific heat @25C	251 J K ⁻¹ kg ⁻¹
Thermal conductivity @0-100C	138 W m ⁻¹ K ⁻¹

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline
Bulk modulus			261.2 GPa
Hardness - Vickers	200	250	
Poisson's ratio			0.293
Tensile modulus			324.8 GPa
Tensile strength	485-550	620-690	MPa
Yield strength	415-450	550	MPa



Mesh

MO008720 Nominal Aperture..... **0.44mm** Wire diameter..... **0.07mm**
 Wires/inch..... **50** Open area **67%**
 Type **Plain weave mesh**

Size		Quantity		
Web Code	Size	1pc	2pcs	5pcs
170-661-784	50 x 50 mm	£ 128.00	£ 163.00	£ 305.00
332-723-333	100 x 100 mm	£ 247.00	£ 426.00	
590-417-407	150 x 150 mm	£ 466.00		

MO008710 Nominal Aperture..... **0.8mm** Wire diameter..... **0.18mm**
 Wires/inch..... **26** Open area **67%**
 Type **Plain weave mesh**

Size		Quantity		
Web Code	Size	1pc	2pcs	5pcs
400-158-315	50 x 50 mm	£ 127.00	£ 158.00	£ 293.00
019-794-770	100 x 100 mm	£ 238.00	£ 408.00	
474-337-539	150 x 150 mm	£ 446.00		

Metal - Molybdenum

Nickel

Ni

Discovered by A.F. Cronstedt in 1751 in Stockholm, Sweden.

Nickel is a silver-white metal which occurs mainly in the sulphide and arsenic ores. It is extracted by roasting to NiO and then reducing using carbon. Pure nickel is manufactured by the Mond process, in which impure nickel is reacted with carbon monoxide (CO) to produce Ni(CO)₄, which is then decomposed at 200C to yield 99.99% Ni. Nickel has an abundance of 80 ppm in the earth's crust.

Pure nickel is malleable and ductile, and is resistant to corrosion in air or water, and hence is used as a protective coating. It is readily soluble in dilute acids, but is unaffected by alkalis. Applications for nickel include its use as a constituent of various alloy types; for example, Nichrome (an alloy used for resistance heating elements), Monel (corrosion resistant material), Permalloy (an alloy with high magnetic permeability at low field strength and low hysteresis loss), stainless steel, cupro-nickel, nickel silver, etc. It is also used in coinage, as a protective coating and within food and chemical handling plants.

Nickel is classed as a carcinogen and is also an allergen to some individuals. It is found in many dietary constituents and, as such, is difficult to avoid.

Atomic Properties

Atomic number	28
Atomic radius - Goldschmidt	0.125 nm
Atomic weight	58.69 amu
Crystal structure	Face centred cubic
Electronic structure	Ar 3d ⁸ 4s ²
Photo-electric work function	4.9 eV
Thermal neutron absorption cross-section	4.54 Barns
Valences shown	0, 1, 2, 3

Physical Properties

Boiling point	2732 C
Density @20C	8.9 g cm ⁻³
Melting point	1453 C

Electrical Properties

Electrical resistivity @20C	6.9 µOhmcm
Temperature coefficient @0-100C	0.0068 K ⁻¹
Thermal emf against Pt (cold 0C - hot 100C)	-1.48 mV

Natural isotope distribution

Mass No.	%
58	68.27
60	26.10
61	1.13
62	3.59
64	0.91

Thermal Properties

Coefficient of thermal expansion @0-100C	13.3 x 10 ⁻⁶ K ⁻¹
Latent heat of evaporation	6378 J g ⁻¹
Latent heat of fusion	292 J g ⁻¹
Specific heat @25C	444 J K ⁻¹ kg ⁻¹
Thermal conductivity @0-100C	90.9 W m ⁻¹ K ⁻¹

Ionisation potential

No.	eV
1	7.63
2	18.2
3	35.2
4	54.9
5	75.5
6	108

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline
Bulk modulus			177.3 GPa
Hardness - Brinell	100	190	
Izod toughness	160	160	J m ⁻¹
Poisson's ratio			0.312
Tensile modulus			199.5 GPa
Tensile strength	400	660	MPa
Yield strength	150	480	MPa



Mesh

NI008705



Nominal Aperture..... **0.04mm**
 Wire diameter..... **0.011mm**
 Open area..... **60%**
 Type..... **Electro-formed mesh**

Thickness..... **0.004mm**
 Wires/inch..... **500**
 Purity..... **99.9%**

Size

Web Code	Size
103-706-185	30 x 30 mm
351-220-929	65 x 65 mm
902-615-473	130 x 130 mm

Quantity

1pc	2pcs	5pcs
£ 180.00	£ 233.00	£ 339.00
£ 301.00	£ 403.00	
£ 524.00		

Typical Analysis : Co 8000, Cu <2000, Fe 50, Mg 100, Mn 50, Si 200, Ti 50, C 160, S 60. Purity includes Cobalt.

NI008711



Nominal Aperture..... **0.34mm**
 Wire diameter..... **0.041mm**
 Open area..... **83%**
 Type..... **Electro-formed mesh**

Thickness..... **0.025mm**
 Wires/inch..... **70**
 Purity..... **99.9%**

Size

Web Code	Size
379-395-065	30 x 30 mm
553-718-329	65 x 65 mm
214-797-774	130 x 130 mm
849-713-797	260 x 260 mm

Quantity

1pc	2pcs	5pcs	10pcs
£ 144.00	£ 181.00	£ 256.00	£ 346.00
£ 221.00	£ 289.00	£ 427.00	
£ 363.00	£ 491.00		
£ 648.00			

Typical Analysis : Co 8000, Cu <2000, Fe 50, Mg 100, Mn 50, Si 200, Ti 50, C 160, S 60. Purity includes Cobalt.

NI008720



Nominal Aperture..... **0.43mm**
 Wire diameter..... **0.067mm**
 Open area..... **75%**
 Type..... **Electro-formed mesh**

Thickness..... **0.004mm**
 Wires/inch..... **51**
 Purity..... **99.9%**

Size

Web Code	Size
370-188-630	30 x 30 mm
214-212-683	60 x 60 mm
712-480-136	60 x 120 mm
776-578-885	120 x 120 mm
072-351-311	240 x 240 mm

Quantity

1pc	2pcs	5pcs	10pcs
£ 130.00	£ 164.00	£ 234.00	£ 318.00
£ 189.00	£ 248.00	£ 367.00	
£ 239.00	£ 318.00		
£ 308.00	£ 417.00		
£ 547.00			

Typical Analysis : Co 8000, Cu <2000, Fe 50, Mg 100, Mn 50, Si 200, Ti 50, C 160, S 60. Purity includes Cobalt.

Nickel

Ni



Mesh

NI008750

Nominal Aperture..... **0.73mm**
 Wires/inch..... **26x26**
 Purity..... **99.0%**

Wire diameter..... **0.25mm**
 Open area **55%**
 Type **Plain weave mesh**



Size

Web Code
 043-915-916

Size	Quantity		
	1pc	2pcs	5pcs
100 x 250 mm	£ 155.00	£ 204.00	£ 303.00

Typical Analysis : Cu <2500, Fe <4000, Mg <2000, Mn <3500, Si <1500, Ti <1000, C <1500, S <100. Total purity includes Cobalt.

Platinum

Pt

Platinum was known to native South Americans before the arrival of Columbus and was introduced into Europe around 1750.

Platinum is a member of the platinum group metals and is lustrous, malleable and ductile; it has an abundance of approximately 0.001 ppm in the earth's crust. Of the group of six metals (Pt, Pd, Os, Ir, Rh and Ru), it is the most important. It is unaffected by oxygen and water and is only soluble in aqua regia or fused alkalis.

Applications for platinum are many and varied; for example, it is used to make weights and measures standards, it is used in the electronics industry for electrical contacts which might be subject to high temperatures, and it is used to manufacture electrodes which might be subject to chemical attack. A current and important use of platinum is in car exhaust catalysts, in which a ceramic honeycomb is coated with platinum. Platinum is also used to manufacture jewellery and, along with gold and silver, has its own hallmark.

Atomic Properties

Atomic number	78
Atomic radius - Goldschmidt	0.138 nm
Atomic weight	195.08 amu
Crystal structure	Face centred cubic
Electronic structure	Xe 4f ¹⁴ 5d ⁹ 6s ¹
Photo-electric work function	5.3 eV
Thermal neutron absorption cross-section	9.0 Barns
Valences shown	1, 2, 3, 4

Physical Properties

Boiling point	3827 C
Density @20C	21.45 g cm ⁻³
Melting point	1772 C

Electrical Properties

Electrical resistivity @20C	10.58 µOhmcm
Temperature coefficient @0-100C	0.00392 K ⁻¹

Thermal Properties

Coefficient of thermal expansion @0-100C	9.0 x10 ⁻⁶ K ⁻¹
Latent heat of evaporation	2405 J g ⁻¹
Latent heat of fusion	101 J g ⁻¹
Specific heat @25C	133 J K ⁻¹ kg ⁻¹
Thermal conductivity @0-100C	71.6 W m ⁻¹ K ⁻¹

Natural isotope distribution

Mass No.	%
190	0.01
192	0.79
194	32.90
195	33.80
196	25.30
198	7.20

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline	
Bulk modulus			276	GPa
Hardness - Vickers	40	100		
Poisson's ratio			0.39	
Tensile modulus			170	GPa
Tensile strength	125-150	200-300		MPa
Yield strength	14-35	185		MPa



Mesh

PT008720

Nominal Aperture..... **0.12mm**
 Wires/inch..... **152**
 Purity..... **99.9%**

Wire diameter..... **0.04mm**
 Open area **56%**
 Type **Plain weave mesh**

Size

Web Code
 382-062-561
 350-210-232
 020-094-727

Size	Quantity		
	1pc	2pcs	5pcs
20 x 20 mm	£ 187.00	£ 239.00	£ 350.00
50 x 50 mm	£ 306.00	£ 500.00	
100 x 100 mm	£ 856.00		

Typical Analysis : Ag 100, Au 75, Cu 50, Fe <50, Ni <100, Pd 150, Rh <20, Si <50.

PT008710

Nominal Aperture..... **0.25mm**
 Wires/inch..... **82x82**
 Purity..... **99.9%**

Wire diameter..... **0.06mm**
 Open area **65%**
 Type **Plain weave mesh**

Size

Web Code
 985-469-901
 183-742-386
 967-797-723

Size	Quantity		
	1pc	2pcs	5pcs
20 x 20 mm	£ 190.00	£ 244.00	£ 358.00
50 x 50 mm	£ 315.00	£ 534.00	
100 x 100 mm	£ 922.00		

Typical Analysis : Ag 100, Au 75, Cu 50, Fe <50, Ni <100, Pd 150, Rh <20, Si <50.

Metal - Nickel

Platinum

Pt



Mesh

PT008705

Nominal Aperture..... **0.4mm**
 Wires/inch..... **52**
 Purity..... **99.9%**

Wire diameter..... **0.1mm**
 Open area **63%**
 Type **Plain weave mesh**

Size

Web Code

512-248-138
 088-167-557
 011-623-035

Size

20 x 20 mm
 50 x 50 mm
 100 x 100 mm

Quantity

1pc	2pcs	5pcs
£ 234.00	£ 302.00	£ 507.00
£ 524.00	£ 950.00	
£ 1747.00		

Typical Analysis : Ag 100, Au 75, Cu 50, Fe <50, Ni <100, Pd 150, Rh <20, Si <50.

Silver

Ag

Silver was known to ancient civilisations.

Silver is a soft, malleable metal with a characteristic sheen. It has the highest thermal and electrical conductivities of all metals. It is generally found uncombined, or in the sulphide or arsenide ores from which it can be recovered as a cyanide complex which is subsequently reduced to the metal, in aqueous solution, by the use of zinc. The pure metal is stable to water and oxygen but is attacked in air by sulphur bearing compounds to form the characteristic black layer of silver sulphide. It is soluble in sulphuric and nitric acids.

Some silver salts are sensitive to light (e.g. AgI, AgCl and AgBr) and are of fundamental importance to photography. Other applications and industries in which silver is used include the manufacture of jewellery (both as the pure metal and as a constituent of various alloys), the electrical industry (e.g. in the manufacture of contacts) and for the silvering of glass.

Atomic Properties

Atomic number 47
 Atomic radius - Goldschmidt 0.144 nm
 Atomic weight 107.8682 amu
 Crystal structure Face centred cubic
 Electronic structure Kr 4d¹⁰ 5s¹
 Photo-electric work function 4.7 eV
 Thermal neutron absorption cross-section 63.8 Barns
 Valences shown 1, 2

Electrical Properties

Electrical resistivity @20C 1.63 µOhmcm
 Temperature coefficient @0-100C 0.0041 K⁻¹
 Thermal emf against Pt (cold 0C - hot 100C) +0.74 mV

Thermal Properties

Coefficient of thermal expansion @0-100C 19.1 x10⁻⁶ K⁻¹
 Latent heat of evaporation 2390 J g⁻¹
 Latent heat of fusion 103 J g⁻¹
 Specific heat @25C 237 J K⁻¹ kg⁻¹
 Thermal conductivity @0-100C 429 W m⁻¹ K⁻¹

Natural isotope distribution

Mass No.	%
107	51.83
109	48.17

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline
Bulk modulus			103.6 GPa
Hardness - Vickers	25	95	
Izod toughness	5 J m ⁻¹		
Poisson's ratio			0.367
Tensile modulus			82.7 GPa
Tensile strength	172	330	MPa

Physical Properties

Boiling point 2212 C
 Density @20C 10.5 g cm⁻³
 Melting point 961.9 C



Mesh

AG008710

Nominal Aperture..... **0.25mm**
 Wires/inch..... **82x82**
 Type **Plain weave mesh**

Wire diameter..... **0.06mm**
 Open area **65%**

Size

Web Code

853-678-745
 526-449-555
 960-337-198

Size

20 x 20 mm
 40 x 40 mm
 80 x 80 mm

Quantity

1pc	2pcs	5pcs
£ 139.00	£ 175.00	£ 245.00
£ 199.00	£ 306.00	
£ 509.00		

Tantalum

Ta

Tantalum was discovered in 1802 by A.G. Ekeberg in Uppsala, Sweden.

Tantalum is a shiny, silvery coloured metal which is heavy, dense, malleable and ductile when pure. It is found in small quantities in minerals (generally in conjunction with niobium), and is isolated by conversion to the oxide and then the fluoro-complex, K_2TaF_7 , from which the pure metal is obtained by electrolysis. Tantalum is extremely corrosion resistant due to the formation of an oxide film, and is also resistant to acid attack (with the exception of HF). It will react with fused alkalis and a variety of non-metals at elevated temperatures.

Tantalum can be used as a replacement for platinum for laboratory apparatus which has to have good corrosion resistance, and the metal is also used within the chemical industry for similar reasons. The fluids in the human body do not react with the metal and, hence, it is used for surgical implants without rejection. Other applications include the use of tantalum carbide in cemented carbides which are used as cutting tools. The pure metal is used in the electronics industry in the manufacture of various types of electronic equipment (e.g. rectifiers, capacitors, lamp filaments, etc.). Tantalum is also used in vacuum systems as it has a high absorption rate for residual gases. It is also used as an alloying element with, for example, nickel and molybdenum, to produce alloys which have good corrosion resistance, strength and ductility.

Atomic Properties

Atomic number	73
Atomic radius - Goldschmidt	0.147 nm
Atomic weight	180.9479 amu
Crystal structure	Body centred cubic
Electronic structure	Xe 4f ¹⁴ 5d ³ 6s ²
Photo-electric work function	4.1 eV
Thermal neutron absorption cross-section	22 Barns
Valences shown	2, 3, 4, 5

Natural isotope distribution	Mass No.	%
	180	0.012
	181	99.988

Ionisation potential	No.	eV
	1	7.88
	2	16.2

Physical Properties

Boiling point	5425 C
Density @20C	16.6 g cm ⁻³
Melting point	2996 C

Electrical Properties

Electrical resistivity @20C	13.5 μ Ohmcm
Temperature coefficient @0-100C	0.0035 K ⁻¹
Superconductivity critical temperature	4.47 K
Thermal emf against Pt (cold 0C - hot 100C)	+0.33 mV

Thermal Properties

Coefficient of thermal expansion @0-100C	6.5 x10 ⁻⁶ K ⁻¹
Latent heat of evaporation	4165 J g ⁻¹
Latent heat of fusion	174 J g ⁻¹
Specific heat @25C	140 J K ⁻¹ kg ⁻¹
Thermal conductivity @0-100C	57.5 W m ⁻¹ K ⁻¹

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline
Bulk modulus			196.3 GPa
Hardness - Vickers	90	200	
Poisson's ratio			0.342
Tensile modulus			185.7 GPa
Tensile strength	172-207	760	MPa
Yield strength	310-380	705	MPa



Mesh

TA008710

Nominal Aperture..... **0.43mm**
 Wires/inch..... **50x50**
 Type..... **Plain weave mesh**

Wire diameter..... **0.075mm**
 Open area..... **72%**

Size

Web Code
 020-199-565
 718-168-899
 771-111-087

Size	Quantity		
	1pc	2pcs	5pcs
40 x 40 mm	£ 270.00	£ 348.00	£ 485.00
100 x 100 mm	£ 414.00	£ 552.00	£ 936.00
150 x 150 mm	£ 534.00	£ 812.00	

Titanium

Ti

Titanium was discovered by Rev. William Gregor in 1791 in Creed, Cornwall, England and, independently, by M.H. Klaproth in 1795 in Berlin, Germany.

Titanium is a hard, lustrous, silvery metal which is obtained by magnesium or calcium reduction of the tetrachloride. It is a relatively abundant element, there being 5600 ppm in the earth's crust. It forms a protective oxide coating and, hence, resists corrosion, although powdered metal burns in air. Titanium tends to be inert at low temperatures but will combine with a variety of reagents at elevated temperatures.

Titanium and its alloys are characterised by their lightness, strength and corrosion resistance and are used widely in aerospace applications. In addition, these properties also make the material suitable for medical applications (e.g. replacement hip joints). Titanium dioxide, TiO₂ is used as a white pigment in paints and plastics as it provides great opacity. The same material is also used in the manufacture of heat resisting and durable glass, the TiO₂ replacing certain proportions of the soda. Titanium carbide is used to manufacture cemented carbides.

Atomic Properties

Atomic number	22
Atomic radius - Goldschmidt	0.147 nm
Atomic weight	47.88 amu
Crystal structure	Hexagonal close packed
Electronic structure	Ar 3d ² 4s ²
Photo-electric work function	4.1 eV
Thermal neutron absorption cross-section	6.1 Barns
Valences shown	2, 3, 4

Physical Properties

Boiling point	3287 C
Density @20C	4.5 g cm ⁻³
Melting point	1660 C

Electrical Properties

Electrical resistivity @20C	54 μOhmcm
Temperature coefficient @0-100C	0.0038 K ⁻¹
Superconductivity critical temperature	0.40 K

Natural isotope distribution

Mass No.	%
46	8.0
47	7.5
48	73.7
49	5.5
50	5.3

Thermal Properties

Coefficient of thermal expansion @0-100C	8.9 x10 ⁻⁶ K ⁻¹
Latent heat of evaporation	8893 J g ⁻¹
Latent heat of fusion	365 J g ⁻¹
Specific heat @25C	523 J K ⁻¹ kg ⁻¹
Thermal conductivity @0-100C	21.9 W m ⁻¹ K ⁻¹

Ionisation potential

No.	eV
1	6.82
2	13.6
3	27.5
4	43.3
5	99.2
6	119

Mechanical Properties

Material condition	Annealed	Polycrystalline
Bulk modulus		108.4 GPa
Hardness - Vickers	60	
Izod toughness	61 J m ⁻¹	
Poisson's ratio		0.361
Tensile modulus		120.2 GPa
Tensile strength	230-460 MPa	
Yield strength	140-250 MPa	



Mesh

TI008710

Nominal Aperture..... **0.19mm**
 Wires/inch..... **60x60**
 Weave..... **Twill**

Wire diameter..... **0.23mm**
 Open area **20%**

Size

Web Code
 113-282-527
 160-318-438
 039-809-321

Quantity			
Size	1pc	2pcs	5pcs
50 x 50 mm	£ 222.00	£ 296.00	£ 424.00
100 x 100 mm	£ 308.00	£ 417.00	£ 625.00
150 x 150 mm	£ 394.00	£ 539.00	

TI008720

Nominal Aperture..... **4.3mm**
 Wires/inch..... **4.4x4.4**
 Condition..... **Diamond pattern**

Wire diameter..... **1.5mm**
 Open area **94%**
 Condition..... **Platinised**

Size

Web Code
 293-740-051

Quantity	
Size	1pc
100 x 100 mm	£ 343.00

Tungsten

W

Tungsten was isolated in 1783 by J.J. and F. Elhuyar in Vergara, Spain.

Tungsten metal is lustrous and silvery white in colour, and does not occur naturally (it has an abundance of 1 ppm in the earth's crust). It is found in the ore Wolframite, a tungstate of iron and manganese, $(FeMn)WO_4$, which is converted to the trioxide and then reduced to the metal by reduction in hydrogen (carbon cannot be used as the very stable carbide would result). Tungsten metal is relatively inert, resisting attack by oxygen, acids and alkalis, although it will react with fused, oxidising alkali media. It has the highest melting point of all metals and, when pure, it can be worked with relative ease; however, the presence of impurities renders tungsten extremely brittle and, therefore, difficult to fabricate.

The high melting point of tungsten makes it suitable for use as electric filaments (e.g. in electric light bulbs). It is also the basis of a range of alloys containing tungsten, copper and nickel which are used for radiation shielding as they provide a 50% increase in density compared to lead. Tungsten and its alloys also find uses in military applications (e.g. armour and shells), as well as counter-balance materials. Tungsten carbide powder (with possible additions of titanium and tantalum carbides) along with nickel or cobalt powders, are compressed and sintered to produce cemented carbides. These products are used in place of high speed steel to form the tip of cutting and drilling tools, or for parts which will be subjected to heavy usage.

Atomic Properties

Atomic number	74
Atomic radius - Goldschmidt	0.141 nm
Atomic weight	183.85 amu
Crystal structure	Body centred cubic
Electronic structure	Xe $4f^{14} 5d^4 6s^2$
Photo-electric work function	4.55 eV
Thermal neutron absorption cross-section	18.5 Barns
Valences shown	2, 3, 4, 5, 6

Electrical Properties

Electrical resistivity @20C	5.4 $\mu\Omega\text{mcm}$
Temperature coefficient @0-100C	0.0048 K^{-1}
Superconductivity critical temperature	0.0154 K
Thermal emf against Pt (cold 0C - hot 100C)	+ 1.12 mV

Thermal Properties

Coefficient of thermal expansion @0-100C	4.5 $\times 10^{-6} K^{-1}$
Latent heat of evaporation	4009 $J g^{-1}$
Latent heat of fusion	192 $J g^{-1}$
Specific heat @25C	133 $J K^{-1} kg^{-1}$
Thermal conductivity @0-100C	173 $W m^{-1} K^{-1}$

Natural isotope distribution

Mass No.	%
180	0.1
182	26.3
183	14.3
184	30.7
186	28.6

Mechanical Properties

Material condition	Soft	Hard	Polycrystalline
Bulk modulus			311 GPa
Hardness - Vickers	360	500	
Poisson's ratio			0.28
Tensile modulus			411 GPa
Tensile strength	550-620	1920	MPa
Yield strength	550 MPa		

Ionisation potential

No.	eV
1	7.98
2	17.7

Physical Properties

Boiling point	5660 C
Density @20C	19.3 $g cm^{-3}$
Melting point	3410 C



Mesh

W 008710

Nominal Aperture..... **0.15mm**
 Wires/inch..... **150**
 Purity..... **99.95%**

Wire diameter..... **0.02mm**
 Open area..... **75%**
 Type..... **Plain weave mesh**

Size

Web Code
 801-794-103
 930-078-183

Quantity		
Size	1pc	2pcs
50 x 50 mm	£ 172.00	£ 281.00
100 x 100 mm	£ 507.00	

Typical Analysis : Al 10, Ca <10, Cd <2, Cr <5, Cu <10, Fe 20, K 50, Mg <4, Mo 40, Na 5, Ni <10, Rb 2, Si 45, H 3, N 6, O 15, S 5.

W 008720

Nominal Aperture..... **0.2mm**
 Wires/inch..... **100**
 Purity..... **99.95%**

Wire diameter..... **0.05mm**
 Open area..... **64%**
 Type..... **Plain weave mesh**

Size

Web Code
 396-167-242
 273-947-026
 748-232-395

Quantity			
Size	1pc	2pcs	5pcs
50 x 50 mm	£ 132.00	£ 175.00	£ 336.00
100 x 100 mm	£ 267.00	£ 498.00	
150 x 150 mm	£ 548.00		

Typical Analysis : Al 10, Ca <10, Cd <2, Cr <5, Cu <10, Fe 20, K 50, Mg <4, Mo 40, Na 5, Ni <10, Rb 2, Si 45, H 3, N 6, O 15, S 5.

Stainless Steel - AISI 304

Fe/Cr18/Ni10

Stainless steels are iron based alloys containing at least 10.5% Chromium. They achieve their stainless characteristics through the formation of an invisible and adherent Chromium rich oxide film. Alloy 304 is a general purpose austenitic stainless steel with a face centered cubic structure. It is essentially non-magnetic in the annealed condition and can only be hardened by cold working. The lower Carbon content compared with alloy 302 gives better corrosion resistance in welded structures.

Physical Properties

Density 7.93 g cm⁻³
 Melting point 1400-1455 C

Thermal Properties

Coefficient of thermal expansion @20-100C 18.0 x10⁻⁶ K⁻¹
 Thermal conductivity @23C 16.3 W m⁻¹ K⁻¹

Electrical Properties

Electrical resistivity 70-72 µOhmcm

Mechanical Properties

Elongation at break < 60 %
 Hardness - Brinell 160-190
 Izod impact strength 20-136 J m⁻¹
 Modulus of elasticity 190-210 GPa
 Tensile strength 460-1100 MPa



Mesh

FE228710

Nominal Aperture..... **0.38mm**
 Wire diameter..... **0.25mm**
 Open area **37%**

Thickness **0.75mm**

Wires/inch..... **40x40**
 Type **Plain weave mesh**



Size

Web Code

530-570-990
 321-365-009
 170-634-909
 329-370-596
 171-322-395

Size

100 x 100 mm
 150 x 150 mm
 300 x 300 mm
 600 x 600 mm
 900 x 900 mm

Quantity

1pc	2pcs	5pcs	10pcs
£ 90.50	£ 109.00	£ 156.00	£ 205.00
£ 101.00	£ 125.00	£ 180.00	
£ 134.00	£ 171.00	£ 254.00	
£ 200.00	£ 264.00		
£ 266.00	£ 358.00		

FE228720

Nominal Aperture..... **0.54mm**
 Wire diameter..... **0.30mm**
 Open area **37%**

Thickness **0.6mm**

Wires/inch..... **30x30**
 Type **Plain weave mesh**



Size

Web Code

224-156-993
 994-243-124
 487-436-354
 580-212-317
 505-502-859

Size

100 x 100 mm
 150 x 150 mm
 300 x 300 mm
 600 x 600 mm
 900 x 900 mm

Quantity

1pc	2pcs	5pcs	10pcs
£ 96.00	£ 115.00	£ 153.00	£ 219.00
£ 116.00	£ 143.00	£ 198.00	
£ 177.00	£ 229.00	£ 333.00	
£ 298.00	£ 400.00		
£ 419.00	£ 572.00		

Stainless Steel - AISI 316

Fe/Cr18/Ni10/Mo 3

Stainless steels are iron based alloys containing at least 10.5% Chromium. They achieve their stainless characteristics through the formation of an invisible and adherent Chromium rich oxide film. Alloy 316 is a general purpose austenitic stainless steel with a face centered cubic structure. It is essentially non-magnetic in the annealed condition and can only be hardened by cold working. Molybdenum has been added to increase corrosion resistance particularly in chloride containing environments, and the lower Carbon content of alloy 316L gives even better corrosion resistance in welded structures.

Physical Properties

Density 7.96 g cm⁻³
 Melting point 1370-1400 C

Thermal Properties

Coefficient of thermal expansion @20-100C 16-18 x10⁻⁶ K⁻¹
 Specific heat @23C 502 J K⁻¹ kg⁻¹
 Thermal conductivity @23C 16.3 W m⁻¹ K⁻¹

Electrical Properties

Electrical resistivity 70-78 µOhmcm
 Temperature coefficient - K⁻¹

Mechanical Properties

Elongation at break < 60 %
 Hardness - Brinell 160-190
 Izod impact strength 20-136 J m⁻¹
 Modulus of elasticity 190-210 GPa
 Tensile strength 460-860 MPa



Mesh

FE248703

Nominal Aperture..... **0.085mm**
 Wires/inch..... **188x188**
 Type **Plain weave mesh**

Wire diameter..... **0.05mm**

Open area **39.6%**



Size

Web Code

387-491-021
 907-193-870
 472-118-700
 764-746-487

Size

100 x 100 mm
 150 x 150 mm
 300 x 300 mm
 600 x 600 mm

Quantity

1pc	2pcs	5pcs	10pcs
£ 160.00	£ 185.00	£ 240.00	£ 297.00
£ 182.00	£ 215.00	£ 289.00	
£ 246.00	£ 307.00		
£ 407.00			

Stainless Steel - AISI 316

Fe/Cr18/Ni10/Mo 3



Mesh

FE248705

Nominal Aperture..... **0.103mm**
 Wires/inch..... **150x150**
 Type **Plain weave mesh**

Wire diameter..... **0.066mm**
 Open area **37%**



Size

Web Code
 688-485-215
 707-822-407
 366-118-058

Size
 150 x 150 mm
 300 x 300 mm
 600 x 600 mm

Quantity

1pc	2pcs	5pcs
£ 128.00	£ 161.00	£ 235.00
£ 192.00	£ 253.00	
£ 353.00		

FE248710

Nominal Aperture..... **0.38mm**
 Wires/inch..... **40x40**
 Type **Plain weave mesh**

Wire diameter..... **0.25mm**
 Open area **37%**



Size

Web Code
 087-878-424
 984-806-837
 100-862-188
 607-766-689

Size
 100 x 100 mm
 150 x 150 mm
 300 x 300 mm
 600 x 600 mm

Quantity

1pc	2pcs	5pcs
£ 100.00	£ 122.00	£ 172.00
£ 118.00	£ 148.00	£ 213.00
£ 173.00	£ 225.00	
£ 283.00		

Monel[®] alloy 400

Ni65/Cu33/Fe 2

Common Brand Names : MONEL[®] alloy 400

High tensile strength Nickel/Copper alloy highly resistant to atmospheric corrosion, salt water and a variety of acid and alkaline solutions. Used in marine engineering, chemical and hydrocarbon processing equipment, valves, pumps and heat exchangers.

Physical Properties

Density 8.84 g cm⁻³
 Melting point 1300-1350 C

Thermal Properties

Coefficient of thermal expansion @20-100C 13.9-14.1 x10⁻⁶ K⁻¹
 Maximum use temperature in air 450 C
 Thermal conductivity @23C 21.7 W m⁻¹ K⁻¹

Electrical Properties

Electrical resistivity 48-51 µOhmcm
 Temperature coefficient 0.0019 K⁻¹

Mechanical Properties

Elongation at break < 40 %
 Hardness - Brinell 125-190
 Izod impact strength 110-140 J m⁻¹
 Modulus of elasticity 185 GPa
 Tensile strength 550-950 MPa



Mesh

NI118710

Nominal Aperture..... **0.38mm**
 Wires/inch..... **40x40**
 Type **Plain weave mesh**

Wire diameter..... **0.25mm**
 Open area **37%**



Size

Web Code
 839-153-657
 894-208-349
 776-040-596

Size
 100 x 100 mm
 150 x 150 mm
 300 x 300 mm

Quantity

1pc	2pcs	5pcs	10pcs
£ 86.00	£ 102.00	£ 141.00	£ 179.00
£ 97.50	£ 118.00	£ 167.00	£ 215.00
£ 131.00	£ 167.00	£ 243.00	

Palladium/Nickel

Pd95/Ni 5



Mesh

PJ088710

Nominal Aperture..... **0.20mm**
 Wires/inch..... **92**
 Type **Plain weave mesh**

Wire diameter..... **0.076mm**
 Open area **52.5%**



Size

Web Code
 555-892-609
 043-768-535
 386-885-208

Size
 20 x 20 mm
 50 x 50 mm
 100 x 100 mm

Quantity

1pc	2pcs	5pcs
£ 150.00	£ 176.00	£ 254.00
£ 284.00	£ 444.00	
£ 762.00		

Platinum/Iridium

Pt90/Ir10

The alloy has been used in "non-standard" thermocouples, electrical contacts and for electrodes in medical research. The alloy is harder and mechanically stronger than Platinum.

Physical Properties

Density 21.56 g cm⁻³
 Melting point 1800 C

Thermal Properties

Coefficient of thermal expansion @20-100C 8.7 x10⁻⁶ K⁻¹
 Thermal conductivity @23C 31 W m⁻¹ K⁻¹

Electrical Properties

Electrical resistivity 25 µOhmcm
 Temperature coefficient 0.0013 K⁻¹

Mechanical Properties

Elongation at break < 25 %
 Hardness - Brinell 130-190
 Tensile strength 380-620 MPa



Mesh

PT028720

Nominal Aperture..... **0.125mm**
 Wires/inch..... **150x150**

Wire diameter..... **0.043mm**
 Weave..... **Plain**

Size

Web Code
 761-010-165

Size	Quantity
34 x 77 mm	1pc POA

One piece only remaining.

Alloy – Platinum/Iridium

Ethylene-Tetrafluoroethylene Copolymer

ETFE

Common Brand Names : Tefzel, Hostafion ET

An expensive, semi-crystalline, melt processable thermoplastic that is essentially a 1:1 alternating copolymer of ethylene and tetrafluoroethylene. It has a very high impact strength even at low temperatures and is relatively stiff by fluoropolymer standards, but its chemical resistance, though good, is not as good as that of PTFE.

It is used for chemical apparatus and process equipment, vessel linings and wire coatings.

Physical Properties

Density	1.7 g cm ⁻³
Flammability	V0
Limiting oxygen index	30-32 %
Radiation resistance	Fair
Refractive index	1.403
Resistance to Ultra-violet	Excellent
Water absorption	0-0.03 %

Electrical Properties

Dielectric constant @1MHz	2.6
Dielectric strength	25 kV mm ⁻¹
Dissipation factor @ 1MHz	0.0005
Surface resistivity	> 10 ¹⁴ Ohm/sq
Volume resistivity	10 ¹⁶ Ohmcm

Thermal Properties

Coefficient of thermal expansion	90-170 x10 ⁻⁶ K ⁻¹
Heat-deflection temperature - 0.45MPa	105 C
Heat-deflection temperature - 1.8MPa	70 C
Lower working temperature	< -100 C
Specific heat	1900-2000 J K ⁻¹ kg ⁻¹
Thermal conductivity @23C	0.24 W m ⁻¹ K ⁻¹
Upper working temperature	150-160 C

Mechanical Properties

Elongation at break	250-350 %
Hardness - Rockwell	R50
Izod impact strength	> 1000 J m ⁻¹
Tensile modulus	0.8 GPa
Tensile strength	28-48 MPa

Chemical Resistance

Acids - concentrated	Good
Acids - dilute	Good
Alcohols	Good
Alkalis	Good
Aromatic hydrocarbons	Good
Greases and Oils	Good
Halogenated Hydrocarbons	Good
Halogens	Good
Ketones	Good



Mesh

FP368703

Nominal Aperture..... **85µm**
 Threads/cm **60.7**
 Type **Plain weave mesh**

Monofilament diameter ... **80µm**
 Open area **26.5%**



Size

Web Code
 299-642-463

Size
 100 x 100 mm

Quantity

1pc
 £ 89.50

FP368705

Nominal Aperture..... **300µm**
 Threads/cm **20**
 Type **Plain weave mesh**

Monofilament diameter ... **200µm**
 Open area **36%**



Size

Web Code
 939-461-139
 432-639-967

Size
 250 x 250 mm
 500 x 500 mm

Quantity

1pc **2pcs** **5pcs**
 £ 107.00 £ 141.00 £ 191.00
 £ 154.00 £ 207.00

FP368710

Nominal Aperture..... **1000µm**
 Threads/cm **6.7**
 Type **Plain weave mesh**

Monofilament diameter ... **500µm**
 Open area **44%**



Size

Web Code
 079-988-126
 998-514-062

Size
 250 x 250 mm
 500 x 500 mm

Quantity

1pc **2pcs** **5pcs**
 £ 119.00 £ 158.00 £ 217.00
 £ 178.00 £ 241.00

Polymer – Ethylene-Tetrafluoroethylene Copolymer

Polyamide - Nylon 6, 6

PA 6,6

Common Brand Names : Akulon S, Maranyl A, Utramid A, Zytel

General Information for 'Nylons'

A family of similar semi-crystalline engineering thermoplastics generally synthesised from straight chain aliphatic acids and amines. Each particular nylon is described by one or two numbers eg nylon 6 or 6,6 where the number is the number of carbon atoms in the amine and acid monomers. Where a single number is used the monomer is an Alpha amino-acid (or its lactam) and the amide links in the polymer are all "head-to-tail". Where two numbers are used the monomers are a diamine and diacid and the amide links alternate "head-to-tail"/"tail-to-head". The first number refers to the diamine, the second to the diacid. Some nylons use aromatic monomers which are denoted by letters eg T for terephthalic and I for isophthalic components.

Nylons generally are strong, tough (but notch-sensitive), rather resilient polymers with good barrier properties and high fatigue and abrasion resistance. However, they have high water absorption (slow in thick sections) accompanied by an increase in dimensions which can be as much as 3% under extreme circumstances. Nylons have good resistance to oils, greases, solvents and alkalis but not to acids which tend to hydrolyse them. The most common nylons are 6 and 6,6 and in the individual descriptions the others are described in relation to them.

General Description of Nylon 6,6 : A semi-crystalline, off-white engineering thermoplastic that is the strongest and most abrasion resistant unreinforced aliphatic nylon with better low temperature toughness than Nylon 6 or acetal. Its very low melt viscosity can give industrial processing difficulties and weathering can cause embrittlement and colour change unless it is stabilised or protected. Available with a wide range of fillers notably glass fibre, which gives a marked increase in stiffness, and solid and liquid (oil) lubricants. Super-tough grades are also available whose impact properties and low notch sensitivity are amongst the best of all engineering thermoplastics.

Applications include mainly engineering components eg gears, bearings, nuts, bolts, rivets and wheels and power tool casings and rocker box covers. Widely used as monofilament for brushes etc and fibre - notable for its resilience and high abrasion resistance - for apparel, carpet and industrial end-uses.

Physical Properties

Density	1.14 g cm ⁻³
Flammability	HB
Limiting oxygen index	23 %
Radiation resistance	Fair
Refractive index	1.53
Resistance to Ultra-violet	Poor
Water absorption	8.5 %
Water absorption - equilibrium	8 %
Water absorption - over 24 hours	2.3 %

Electrical Properties

Dielectric constant @1MHz	3.4
Dielectric strength	25 kV mm ⁻¹
Dissipation factor @ 1kHz	0.2
Surface resistivity	10 ¹¹ Ohm/sq
Volume resistivity	10 ¹³ Ohmcm

Thermal Properties

Coefficient of thermal expansion	90 x10 ⁻⁶ K ⁻¹
Heat-deflection temperature - 0.45MPa	200 C
Heat-deflection temperature - 1.8MPa	100 C
Lower working temperature	-30 C
Specific heat	1670 J K ⁻¹ kg ⁻¹
Thermal conductivity @23C	0.25 W m ⁻¹ K ⁻¹
Upper working temperature	80-180 C

Mechanical Properties

Abrasive resistance - ASTM D1044	3-5 mg/1000 cycles
Coefficient of friction	0.2-0.3
Elongation at break	40 %
Hardness - Rockwell	M89
Izod impact strength	40-110 J m ⁻¹
Poisson's ratio	0.41
Tensile modulus	3.3 GPa
Tensile strength	82 MPa

Chemical Resistance

Acids - concentrated	Poor
Acids - dilute	Poor
Alcohols	Good
Alkalis	Good-Fair
Aromatic hydrocarbons	Good
Greases and Oils	Good
Halogenated Hydrocarbons	Good-Poor
Halogens	Poor
Ketones	Good



Mesh

AM328710 Nominal Aperture..... **50µm**
 Threads/cm **110**
 Type **Plain weave mesh**

Monofilament diameter ... **39µm**
 Open area **32%**

Size Web Code	Size	Quantity		
		1pc	2pcs	5pcs
105-345-752	250 x 250 mm	£ 80.50	£ 96.50	£ 125.00
168-214-136	500 x 500 mm	£ 101.00	£ 126.00	

Polymer – Polyamide - Nylon 6, 6

Polyetheretherketone

PEEK

Common Brand Names : Victrex PEEK, Zyx, Vestakeep

General Description : A high performance thermoplastic with the characteristics common to this group - strong, stiff, hard, high temperature resistance, good chemical resistance and inherently low flammability and smoke emission. PEEK is pale amber in colour and usually semi-crystalline and opaque, except thin films are usually amorphous and transparent. It also has very good resistance to wear, dynamic fatigue and radiation, but it is difficult to process and very expensive. Filled grades, including ones designed for bearing-type applications, are also used.

Applications include flexible printed circuit boards (film), fibres and monofilaments, injection moulded engineering components and items used in aerospace and radiation environments.

Physical Properties

Density	1.26 - 1.32 g cm ⁻³
Flammability	V-0 @ 1.5mm
Limiting oxygen index	35 %
Radiation resistance	Good
Resistance to Ultra-violet	Fair
Water absorption - equilibrium	0.5 %
Water absorption - over 24 hours	0.1-0.3 %

Elongation at break	50 %
Hardness - Rockwell	M99
Izod impact strength	85 J m ⁻¹
Poisson's ratio	0.4
Tensile modulus	3.7-4.0 GPa
Tensile strength	70-100 MPa

Electrical Properties

Dielectric constant @1kHz	3.2-3.3 @ 50Hz-10KHz
Dielectric strength	190 @ 50µm kV mm ⁻¹
Dissipation factor @ 1MHz	0.003
Volume resistivity	10 ¹⁵ -10 ¹⁶ Ohmcm

Chemical Resistance

Acids - concentrated	Good-Poor
Acids - dilute	Good
Alcohols	Good
Alkalis	Good
Aromatic hydrocarbons	Good
Greases and Oils	Good
Halogenated Hydrocarbons	Good
Halogens	Good-Poor
Ketones	Good-Poor

Thermal Properties

Coefficient of thermal expansion	47/108 x10 ⁻⁶ K ⁻¹
Heat-deflection temperature - 0.45MPa	> 260 C
Heat-deflection temperature - 1.8MPa	160 C
Specific heat	1340 J K ⁻¹ kg ⁻¹
Thermal conductivity @23C	0.25 W m ⁻¹ K ⁻¹
Upper working temperature	250 C

Mechanical Properties

Coefficient of friction	0.18
-------------------------	------



Mesh

EK308704	Nominal Aperture.....	300µm	Monofilament diameter ...	200µm	
	Threads/cm	19	Open area	36%	
	Type	Plain weave mesh			
	Size		Quantity		
Web Code		Size	1pc	2pcs	5pcs
572-572-082		150 x 150 mm	£ 96.00	£ 118.00	£ 159.00
789-529-220		300 x 300 mm	£ 137.00	£ 197.00	
879-001-504		600 x 600 mm	£ 328.00		

EK308730	Nominal Aperture.....	300µm	Monofilament diameter ...	200µm			
	Threads/cm	19	Open area	36%			
	Type	Plain weave mesh					
	Size		Quantity				
Web Code		Size	1pc	2pcs	5pcs	10pcs	20pcs
610-973-841		100 x 100 mm	£ 67.50	£ 80.00	£ 132.00	£ 218.00	£ 389.00
606-672-189		150 x 150 mm	£ 84.00	£ 122.00	£ 237.00	£ 429.00	
283-158-180		300 x 300 mm	£ 198.00	£ 350.00	£ 808.00	£ 1570.00	
852-868-308		600 x 600 mm	£ 654.00	£ 1263.00	£ 3089.00		
019-457-955		1000 x 1000 mm	£ 1736.00	£ 3427.00			

EK308705	Nominal Aperture.....	450µm	Monofilament diameter ...	200µm	
	Threads/cm	13.5	Open area	48%	
	Type	Plain weave mesh			
	Size		Quantity		
Web Code		Size	1pc	2pcs	5pcs
346-012-625		100 x 100 mm	£ 84.50	£ 103.00	£ 134.00
239-077-194		150 x 150 mm	£ 99.50	£ 124.00	£ 169.00
357-303-011		250 x 250 mm	£ 129.00	£ 173.00	
637-292-099		300 x 300 mm	£ 144.00	£ 223.00	

EK308710	Nominal Aperture.....	1100µm	Monofilament diameter ...	400µm	
	Threads/cm	6.3	Open area	54%	
	Type	Plain weave mesh			
	Size		Quantity		
Web Code		Size	1pc	2pcs	5pcs
169-860-777		125 x 125 mm	£ 96.50	£ 144.00	£ 275.00
860-936-798		250 x 250 mm	£ 221.00	£ 392.00	
617-097-111		500 x 500 mm	£ 717.00		

Polyethylene terephthalate

Polyester, PET, PETP

Common Brand Names : Arnite, Dacron, Hostaphan, Impet, Melinar, Melinex, Mylar, Rynite, Terylene, Trevira

General Description: The most common thermoplastic polyester, this polymer is often called just "polyester". This often causes confusion - not only is the chemically similar PBT also a (thermoplastic) polyester, the most common resin system used in GRP is also a polyester system - and also often called just "polyester". (In this latter case, however, the polyesters are chemically unsaturated and are "free-radical polymerised" into a thermoset).

PET is a hard, stiff, strong, dimensionally stable material that absorbs very little water. It has good gas barrier properties and good chemical resistance except to alkalis (which hydrolyse it). Its crystallinity varies from amorphous to fairly high crystalline; it can be highly transparent and colourless but thicker sections are usually opaque and off-white.

It is widely known in the form of biaxially oriented and thermally stabilised films usually referred to by their main brand names Mylar, Melinex or Hostaphan. Strictly speaking, these names should be used only for this type of film whose properties are different from, and in several respects superior to, those of "ordinary" PET film.

These "Mylar[®]-type" films are used for capacitors, graphics, film base and recording tapes etc. PET is also used for fibres for a very wide range of textile and industrial uses (Dacron[®], Trevira[®], Terylene[®]). Other applications include bottles and electrical components.

Physical Properties

Density	1.3-1.4 g cm ⁻³
Flammability	HB
Limiting oxygen index	21
Radiation resistance	Good
Refractive index	1.58-1.64
Resistance to Ultra-violet	Fair?
Water absorption - equilibrium	< 0.7 %
Water absorption - over 24 hours	0.1 %

Electrical Properties

Dielectric constant @1MHz	3.0
Dielectric strength	17 kV mm ⁻¹
Dissipation factor @ 1kHz	0.002
Surface resistivity	10 ¹³ Ohm/sq
Volume resistivity	> 10 ¹⁴ Ohmcm

Thermal Properties

Coefficient of thermal expansion	20-80 x10 ⁻⁶ K ⁻¹
Heat-deflection temperature - 0.45MPa	115 C
Heat-deflection temperature - 1.8MPa	80 C
Lower working temperature	-40 to -60 C
Specific heat	1200 - 1350 J K ⁻¹ kg ⁻¹
Thermal conductivity @23C	0.15-0.4 W m ⁻¹ K ⁻¹
Upper working temperature	115-170 C

Mechanical Properties

Coefficient of friction	0.2-0.4
Hardness - Rockwell	M94-101
Izod impact strength	13-35 J m ⁻¹
Poisson's ratio	0.37-0.44(oriented)
Tensile modulus	2-4 GPa
Tensile strength	80, for biax film 190-260 MPa

Chemical Resistance

Acids - concentrated	Good-Poor
Acids - dilute	Good
Alcohols	Good
Alkalis	Poor
Aromatic hydrocarbons	Good-Fair
Greases and Oils	Good
Halogenated Hydrocarbons	Good-Poor
Halogens	Fair-Poor
Ketones	Good-Fair



Mesh

ES308704 Nominal Aperture..... **21µm**
 Threads/cm **163**
 Type **Plain weave mesh**

Monofilament diameter ... **41µm**
 Open area **12%**

Size	Web Code	Size	Quantity			
			1pc	2pcs	5pcs	10pcs
	564-052-468	250 x 250 mm	£ 96.00	£ 118.00	£ 158.00	£ 210.00
	061-667-407	500 x 500 mm	£ 131.00	£ 168.00	£ 293.00	

ES308710 Nominal Aperture..... **100µm**
 Threads/cm **55**
 Type **Plain weave mesh**

Monofilament diameter ... **70µm**
 Open area **33%**

Size	Web Code	Size	Quantity			
			1pc	2pcs	5pcs	10pcs
	019-331-299	250 x 250 mm	£ 79.00	£ 94.00	£ 120.00	£ 155.00
	416-401-841	500 x 500 mm	£ 96.00	£ 118.00	£ 166.00	

Polymer – Polyethylene terephthalate

Polypropylene

PP

Common Brand Names : Appryl, Hostalen PP, Lacqtene, Novolen, Propathene

General Description : A semi-crystalline, white, semi-opaque commodity thermoplastic made in a very wide variety of grades and modifications. It is a linear polyolefin which can be compared in many ways to high density polyethylene (HDPE) and that is manufactured in a very similar way. The catalysts used control the polymer's stereoregularity quite well so that commercial polypropylenes (PP) are usually predominantly isotactic. PP homopolymer is harder and has a higher temperature resistance than HDPE but lower impact resistance and becomes brittle below 0°C. Hence copolymer grades are preferred for all applications exposed to cold/winter conditions. These copolymers have better impact strength, maintained down to lower temperatures, than homopolymer at the expense of quite small reductions in other properties. Like polyethylenes, PP has good chemical but poor UV resistance (unless stabilised or protected).

Due to thermal stability issues with materials such as PP, additives such as anti-oxidants are invariably used during processing. It should also be noted that when considering the use of heat sealable films, that this product is in fact a coextruded film, comprising a PP core layer and PP/PE copolymer outer layers. These films are also corona treated to aid adhesion and may well also contain an anti-blocking additive such as silica. If you have any doubts about the suitability of any of these materials, please ask for confirmation prior to placing a purchase order.

Applications include (for homopolymers) appliance housings, housewares, packaging, cassette holders and fibres, monofilaments and slit-film tapes; for copolymers pipes, containers, boat hulls, seat shells and automotive parts e.g. battery cases and bumpers though the latter are often made from more heavily elastomer-modified polypropylenes.

Physical Properties

Density	0.9 g cm ⁻³
Flammability	HB
Limiting oxygen index	18 %
Radiation resistance	Fair
Refractive index	1.49
Resistance to Ultra-violet	Poor
Water absorption - equilibrium	0.03 %

Electrical Properties

Dielectric constant @1MHz	2.2-2.6
Dielectric strength	30-40 kV mm ⁻¹
Dissipation factor @ 1MHz	0.0003 - 0.0005
Surface resistivity	10 ¹³ Ohm/sq
Volume resistivity	10 ¹⁶ -10 ¹⁸ Ohmcm

Thermal Properties

Coefficient of thermal expansion	100-180 x10 ⁻⁶ K ⁻¹
Heat-deflection temperature - 0.45MPa	100-105 C
Heat-deflection temperature - 1.8MPa	60-65 C
Lower working temperature	-10 to -60 C
Specific heat	1700 - 1900 J K ⁻¹ kg ⁻¹
Thermal conductivity @23C	0.1-0.22 W m ⁻¹ K ⁻¹
Upper working temperature	90-120 C

Mechanical Properties

Abrasive resistance - ASTM D1044	13-16 mg/1000 cycles
Coefficient of friction	0.1-0.3
Elongation at break	150-300, for biax film > 50 %
Hardness - Rockwell	R80-100
Izod impact strength	20-100 J m ⁻¹
Tensile modulus	0.9-1.5, for biax film 2.2-4.2, GPa
Tensile strength	25-40, for biax film 130-300, MPa

Chemical Resistance

Acids - concentrated	Good-Fair
Acids - dilute	Good-Fair
Alcohols	Good
Alkalils	Good
Aromatic hydrocarbons	Fair
Greases and Oils	Good-Fair
Halogenated Hydrocarbons	Good-Poor
Halogens	Poor
Ketones	Good



Mesh

PP308706 Nominal Aperture..... **34µm**
 Threads/cm **70**
 Weave..... **Satin**

Monofilament diameter ... **150µm**
 Open area **4%**

Size

Web Code
 766-560-886
 190-032-948

Size	Quantity		
	1pc	2pcs	5pcs
250 x 250 mm	£ 83.00	£ 99.50	£ 129.00
500 x 500 mm	£ 106.00	£ 132.00	

PP308710 Nominal Aperture..... **125µm**
 Threads/cm **43**
 Type **Plain weave mesh**

Monofilament diameter ... **110µm**
 Open area **29%**

Size

Web Code
 755-966-978
 495-866-310

Size	Quantity		
	1pc	2pcs	5pcs
250 x 250 mm	£ 78.50	£ 93.50	£ 120.00
500 x 500 mm	£ 97.00	£ 120.00	

INDEX

A		MONEL [®] alloy 400	31
Akulon S	34	Monel [®] alloy 400 (Ni65/Cu33/Fe 2)	31
Aluminium (Al)	19	Mylar	36
Appryl	37	N	
Arnite	36	Nickel (Ni)	24
B		Novolen	37
Beryllium (Be)	20	P	
C		Palladium/Nickel (Pd95/Ni 5)	31
Copper (Cu)	20	Platinum (Pt)	25
D		Platinum/Iridium (Pt90/Ir10)	32
Dacron	36	Polyamide - Nylon 6, 6 (PA 6,6)	34
E		Polyetheretherketone (PEEK)	35
Ethylene-Tetrafluoroethylene Copolymer (ETFE)	33	Polyethylene terephthalate (Polyester, PET, PETP)	36
G		Polypropylene (PP)	37
Gold (Au)	21	Propathene	37
H		R	
Hostafion ET	33	Rynite	36
Hostalen PP	37	S	
Hostaphan	36	Silver (Ag)	26
I		Stainless Steel - AISI 304 (Fe/Cr18/Ni10)	30
Impet	36	Stainless Steel - AISI 316 (Fe/Cr18/Ni10/Mo 3)	30
L		T	
Lacqtene	37	Tantalum (Ta)	27
M		Tefzel	33
Maranyl A	34	Terylene	36
Melinar	36	Titanium (Ti)	28
Melinex	36	Trevira	36
Mesh		Tungsten (W)	29
.. Aluminium	19	U	
.. Beryllium	20	Ultramid A	34
.. Copper	21	V	
.. Ethylene-Tetrafluoroethylene Copolymer	33	Vestakeep	35
.. Gold	22	Victrex PEEK	35
.. Molybdenum	23	Z	
.. Monel [®] alloy 400	31	Zyex	35
.. Nickel	24	Zytel	34
.. Palladium/Nickel	31		
.. Platinum	25		
.. Platinum/Iridium	32		
.. Polyamide - Nylon 6, 6	34		
.. Polyetheretherketone	35		
.. Polyethylene terephthalate	36		
.. Polypropylene	37		
.. Silver	26		
.. Stainless Steel - AISI 304	30		
.. Stainless Steel - AISI 316	30		
.. Tantalum	27		
.. Titanium	28		
.. Tungsten	29		
.. Molybdenum (Mo)	23		