

Boron Nitride Sputtering Target

Formula: BN

Thickness: 3mm

Diameter: 25.4mm

Production Method: Hot Isostatic Pressed

CAS Number: 10043-11-5

UOM Code: 735-414-82

SKU: 1000035338-group

Product Code: B-60-ST-000100

Material Properties for Ceramics

Chemical Resistance

Element	Value
Acids - concentrated	Fair
Acids - dilute	Fair
Alkalis	Fair
Halogens	Poor
Metals	Good

Electrical Properties

Element	Value
Dielectric constant	4.3
Dielectric strength(kV mm ⁻¹)	40-200
Volume resistivity(Ohmcm)	10 ¹¹ -10 ¹⁷ @25

Physical Properties

Element	Value
Apparent porosity(%)	Feb-15
Density(gcm ⁻³)	1.9-2.2

Thermal Properties

Element	Value
---------	-------

Sublimation point(C)	2600-2800
Upper continuous use temperature(C)	950-2500
Specific heat(J K ⁻¹ kg ⁻¹)	800-2000@25°C
Thermal conductivity(W m ⁻¹ K ⁻¹)	15-50@20°C
Coefficient of thermal expansion(x10 ⁻⁶ K ⁻¹)	1-36@20-1000°C

Mechanical Properties

Element	Value
Tensile modulus(GPa)	20-35
Shear strength(MPa)	Dec-25

Pultrusions

Element	Value
Compressive strength(MPa)	30-120